

PICA CUBE™ 4C

DESIGNED BY THE BLACK TANK



SPECIFICATIONS

Input Voltage:	12-24VDC or 12VAC
Power Consumption:	20 Watt at maximum output
Power Input:	Power Adapter (100-240VAC In/12-24VDC Out) or CAT5 (Power +Data)
LED:	1 x 12W Osram Multi-chip
Lumen Maintenance:	80,000 hours B50 L70 at 45C (LM-79-08 Standard)
Data:	DMX, RJ45 Connectors
Output:	285 lumens
Color Range:	4.2 billion discrete mixes (256 x 256 x 256 x 256)
Operation:	DMX: 8 or 16 bit DMX512/Manual: Rotary Knob
Operating Temp.:	-13° to 113° F (-20° to 45° C)
Humidity:	0 - 95% non-condensing
Dimensions:	2.5in x 2.5in x 3.6 in (63.5mm x 63.5mm x 91mm)
Weight:	0.9 lbs (0.41 kg)
Housing:	Powder Coated Aluminum Extrusion (1/8" wall)
Approvals:	FCC Class A Radiated and Conducted ETL / UL Standards 1573 and 8750 cETL / CSA C22.2 #166-M1983 CE / IP20 Rated

PICA CUBE ACCESSORIES

- Top Hat
- Egg Crate Louver
- Barn Doors (Set of 4)
- Mounting Hardware
- Symmetrical Diffusers
- Asymmetrical Diffusers
- Wall Power Adapter
- Pica Portal 125

PART NUMBERS

4C Black:	515 90200 1014
4C White:	515 90200 2014

WHAT'S IN THE BOX

- Pica Cube
- Set of Homogenizing & Spread Lenses
- Requires Wall Adapter or Pica Portal for power

