



## KEY FEATURES

IP65 for temporary outdoor applications

(4) 60W RGBL LED Array

Up to 4000 Total Lumens Fixture Output

Pixel Control

Calibrated Color Temperature Control

Wide Zoom Range from 5° to 40°

The **REBEL WASH 4™** is a powerful IP65-rated LED wash for many interior and exterior applications.

Projecting up to 4000 lumens output from 4 60W RGBL emitters, the **REBEL WASH 4™** is the ideal work horse luminaire providing high output with powerful beams or wide washes, with excellent color quality. From intense primary colors to excellent white color quality with high CRI and calibrated color temperatures, the fixture is the perfect choice for a wide variety of applications. Pixel control or simple uniform access provide additional levels of excitement and effects, and the 360 degree endless Pan and Tilt rotation allows the fixture add another layer of creativity.

With a fast zoom range from 5° to 40° out of a compact fixture design, the **REBEL WASH 4™** has the complete feature set for a wide variety of shows and events. Fully sealed from dust and water, it is a flexible fixture ready to perform in short-term outdoor applications or any indoor environment.

# REBEL™ WASH 4



4x60W IP65 RGBL Wash Fixture

## SPECIFICATIONS

### SOURCE

(4) 60W RGBL LED  
30,000 Hour Average LED Life\*  
\*Test lab conditions. May vary depending on several factors including but not limited to:  
Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming.

### PHOTOMETRIC DATA

4000 Total Lumen Fixture Output  
CRI - 83.4  
TLCI - 67  
Zoom Range 5° - 40°  
Beam Angle: 5° - 40°  
Field Angle: 8.5° - 56.5°

### EFFECTS

Motorized Zoom  
Pixel Control  
Variable 16-bit Dimming Curves  
High Speed Electronic Shutter and Strobe  
DMX Controllable LED Refresh Rate  
Pan Angle: 360/540°  
Tilt Angle: 360/270°  
Continuous 360° Pan and Tilt Rotation

### COLOR

RGBL Color Array  
CMY Emulation  
Variable CCT 2400K - 8500K  
Virtual Gel Swatch Book

### CONTROL / CONNECTIONS

3 DMX Channel Modes  
DMX, RDM, Art-NET, sACN Protocol Support  
(5) Button Touch Control Panel  
Full Color 180° Reversible LCD Menu Display  
Hibernation Mode (Power Save)  
IP65 Locking 5pin XLR Connector In/Out  
IP65 Locking RJ45 Ethernet Connector In/Out  
IP65 Locking Power Connector In/Thru

### SIZE / WEIGHT

Length: 11.7 in (298 mm)  
Width: 8.1 in (205 mm)  
Height: 14.2 in (360 mm)  
Weight: 19 lbs. (8.6 kg)

### ELECTRICAL

AC 100-240V 50/60Hz  
Max Power Consumption 340W  
Power Thru Capacity: 8A (2 units @115V, 5 units @240V)  
-4° to 113°F (-20°C to 45°C)  
BTU/hr (+/- 10%) 1159.4

### INCLUDED ITEMS

Omega Brackets (x2)  
Safety Cable  
IP65 Rated Locking Power Cable

### APPROVALS / RATINGS

CE | cETLus | FCC | UKCA | IP65



## ORDERING INFORMATION

SKU (US)	SKU (EU)	DESCRIPTION
REB104	1237000394	Elation Rebel Wash 4



Specifications are subject to change without notice ©Elation Professional 10/14/2025  
Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040  
323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands  
+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu



## 4x60W IP65 RGBL Wash Fixture

## DIMENSIONS

