

# TOURNADO 5 COB WIMAX

## 7\* 25W 5-in-1 COB LED IP65 Rated LED PAR

Rocking someone like a hurricane? Been thunderstruck? Making it rain men? No matter what kind of tempest you bring to the stage you need the TOURnado™ WIMAX Series from Blizzard Lighting.

The TOURnado™ WIMAX COB 5 brings more lightning for your thunder with higher output than ever before. Get super bright RGBAW color mixing from 7x 25W 5-in-1 LEDs with wide angle 60° optics.

The TOURnado™ WIMAX COB 5 weathers almost any storm. It's IP65 outdoor rated and sports a larger natural convection cooled cast aluminum housing than previous models. It has a tempered glass lens and watertight internal gaskets. The back has outdoor rated 3-pin XLR data and AC power input/output connectors with rubber seals.

It's time to truly unleash the storm and go wireless. The built-in W-DMX™ receiver works seamlessly with any W-DMX™ product and provides ultra-stable wireless communication for more than 500 meters (line-of-sight)!

All TOURnado™ WIMAX fixtures have a 4-button control panel with an OLED display. You have total control including master/slave settings, 5 auto modes, custom programs (up to 3\* 20 scene programs), fade, strobe, manual color adjustments, multiple user-selectable 32-bit dimming modes and more.

Riders on the storm, time to mount up and experience the TOURnado™ WIMAX COB 5.



**IP65**

SUITABLE FOR OUTDOOR USE

### Main Features

- Color mixing via 7x 25W RGBAW 5-in-1 LEDs
- IP65 rated outdoor LED fixture
- OLED control menu with 4x touch sensitive buttons
- 60-degree beam angle
- Built-in wireless W-DMX™ receiver
- Built-in color & chase macros via DMX
- Built-in automated programs via master/slave
- Color mixing ability in standalone mode
- 5/7/11-channel DMX profiles w/32-bit dimming
- Convection cooled cast aluminum housing
- Dual mounting brackets for positioning flexibility
- Flicker-free constant-current LED driver
- IP rated locking power and 3-pin DMX connections
- Dimensions: 14x6.7x13.3 inches (355x172x337 mm)
- Weight: 17.0 lbs (7.7 kg)



#### Optical

Light Source: 7\* high output 25-watt RGBAW COB LEDs

60° beam angle

Flicker-free LEDs

Luminous Intensity:  
1,614 Lux (150.0 fc) @  
2.5m | 423 Lux (39.3 fc)  
@ 5m



#### Wireless Receiver

Transmission band:  
2.4Ghz ISM (2.4-  
2.525Ghz)

Channels: 512

Receiver sensitivity:  
-94dBm



#### Control

Protocol: USITT DMX-512

5/7/11-channel DMX  
modes

Standalone, master/slave,  
DMX modes

IP65 Seetronic 3-pin DMX  
input/output

4-button OLED control  
menu display



#### Power + Current

100-264VAC, 47-63 Hz

Power Consumption:  
168W, 1.44A, PF: .99



#### Warranty + Certifications

2-year limited warranty,  
does not cover  
malfunction  
caused by damage to  
LEDs

cETLus certified