

The 400F is a high power LED TV fresnel, providing the light output equivalent to a 2000W tungsten fresnel designed specifically for TV broadcast lighting. A very high TLCI rating provides an excellent quality of light, ideal for the camera.

The range includes two color temperatures, 3200K and 5600K in both manual and pole operated formats. Perfect for larger studio use.

FEATURES & BENEFITS


- High TLCI.
- Available as manual and pole operation.
- Shaft focus design, with manual knob at rear and angled pole operation cup at the front.
- 3 selectable FAN modes for complete control silent / brightness / on.
- Selectable LED or "tungsten" response.
- Built-in 3 tungsten dimmer curves for matching legacy lighting.
- Color LCD display.
- Easy "touch & turn" operation with 8 soft buttons and wheel.
- USB port for firmware upgrade and performance log file download.
- Local and DMX control.
- RDM setup.
- powerCON AC and 5 pin DMX in & thru connectors.
- Two year limited warranty.


SOURCE				
overter	Туре	LED		
	Wattage	380W (max)		
OPTICAL	-	500 W (max)		
	Color temperature	3200K 5600K		
		96		
	TLCI	97		
BEAM				
	Beam angle	12-45°		
CONTROL				
	Dimming	Local		
		DMX 8 or 16-bit		
POWER				
	Operating voltage	90-240VAC (auto-ranging)		
	Frequency	50/60Hz 1.73A (max)		
	Current draw			
	Power consumption	380W (max)		
ENVIRON	MENT	°C	°F	
	Ambient temperature	0-37°	32-99°	
	Humidity	0-95% non-condensing		
COOLING				
	Cooling	Fan		
PHYSICAL	_S			
	IP rating	IP20		
	Finish	Black		
	Construction	Aluminium extrusion and casting		
		mm	in	
	Lens size	Ø 250	Ø 9.8	
	Color filter size	Ø 320	Ø 12.6	
		1	1	

DIMENSIONS		mm	in
	Manual operation	435 x 752 x 422	17.1 x 29.6 x 16.6
H x W x D (max)	Pole operation	465 x 752 x 422	18.3 x 29.6 x 16.6
WEIGHT		kg	lb
Maint	Manual operation	14.8	32.6
Weight	Pole operation	17.4	38.4
WARRANTY & APPROBATION			
Warranty		2 years	

Ambient temperature: 25°C Fan operation: silent mode

	5m / 16.5ft		10m / 38ft		15m / 49ft	
	Lux	Spot	Lux	Spot	Lux	Spot
3200K (12°)	7920	0.53	1980	1.05	880	1.58
3200K (45°)	787	2.1	197	4.14	87	6.21
5600K (12°)	8280	0.53	2070	1.05	920	1.58
5600K (45°)	866	2.1	217	4.14	96	6.21





400F	ORDER CODE
Strand 400F manual operation, 3200K	400FTVTUNGMO
Strand 400F manual operation, 5600K	400FTVDAYLTMO
Strand 400F pole operation, 3200K	400FTVTUNGPO
Strand 400F pole operation, 5600K	400FTVDAYLTPO

ACCESSORIES	ORDER CODE
Spare 4 leaf barndoor	200FTVBD

 $\ensuremath{\textcircled{}^\circ}$ 2018 Signify Holding. All rights reserved.

All trademarks are owned by Signify Holding or their respective owners. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Data subject to change.

Ref: 400FTVTUNGMO-SpecSheet-01