

grandMA3 4Port Node PoE

Art.-No. 4010516-1



The grandMA3 4Port Node PoE is the most popular converter for Ethernet to DMX data in a half width, 1RU housing. The Node synchronously outputs 4 DMX universes from any grandMA3 session and is suitable for touring and fixed installations. A unique bracket accessory allows for alternative fixing methods if required.

The PoE version (Power over Ethernet) offers a simple and fast solution for power supply.

Every grandMA3 xPort Node is designed for the ever-increasing demands in touring and fixed installation applications to build a reliable and stable backbone of synchronized data transportation. All Nodes are remotely configurable from any console or onPC station within the session to provide easy access to DMX output or DMX input.

Furthermore, all grandMA3 xPort Nodes are available as an onPC version to provide parameters for standalone onPC stations (for more details see: grandMA3 onPC solutions).

Every grandMA3 xPort Node is capable of handling MA-Net3, MA-Net2, sACN and Art-Net data and is fully RDM compliant. A 3.9" color display on the front face allows for simple configuration and provides a quick overview of the status of each Node.

All grandMA3 xPort Nodes are equipped with a powerful processor and a 1 000 Mbit/s Ethernet connection to ensure the most reliable and stable Ethernet to DMX and vice versa conversion.

The grandMA3 xPort Nodes are high quality solutions that can handle busy Ethernet connections without ditching DMX or RDM messages.

It has never been easier to design and maintain stable DMX capable networks.

Scope of delivery

Art.-No.	Article	Quantity
4025695	MA Quick Manual for grandMA3 Nodes	1

1x powerCON TRUE1 socket (NAC3FX-W-TOP) or similar

Technical Specifications

Parameters	none
Parameters Mode2	none
Operating voltage/ Supply voltage	AC 100 - 240 V; 50/60 Hz PoE (IEEE 802.3af; 48 V DC/max. 12 W)
Power	max. 15 VA
Operating Temperature	0 °C up to 40 °C / 32 °F up to 104 °F
Dimensions	207 x 184 x 43 mm / 9 x 8 x 2 in (width x depth x height)
Net weight	2 kg / 5 lbs
Connectors	1 x powerCON TRUE1 1 x etherCON/RJ45 4 x DMX512-A Out (5pin XLR female) 1 x USB 2.0 (type A)

Article

Art.-No.	Article
4010516-1	grandMA3 4Port Node PoE

Accessories

Art.-No.	Article
130281	MA 2Port Node / 4Port Node 19" rack mounting kit - blank panel
130282	MA 4Port Node 19" rack mounting kit - XLR connectors
130283	MA 2Port Node / 4Port Node 19" rack mounting kit - 2x Nodes
130284	MA 2Port / 4Port / 8Port Node rigging plate
210629	Adapter cable set for MA 4Port Node, 4x cable DMX/XLR5 to DMX (length 0.5m), 1x cable RJ45, 1x built-in socket etherCON/RJ45 to RJ45
210632	Adapter cable set for MA 4Port Node, 4x cable DMX/XLR5 to RJ45 (length 0.5m), 1x cable RJ45, 5x built-in socket etherCON/RJ45 to RJ45
210627	Adapter cable set for MA 2Port / 4Port Node, 4x cable DMX/XLR5 to DMX (length 0.5m)
210628	Adapter cable set for MA 2Port / 4Port Node, 1x cable RJ45, 1x built-in socket etherCON/RJ45 to RJ45

More product pictures

