

DIGITAL AMBIENT NOISE CONTROLLER

DP-L2(CU)

The DP-L2 is a digital audio processor equipped with 2 X Input, 2 X Output, 1 X ambient noise sensor microphone input and 1 X monitor output and features easy setting of each function by the front panel operation. It is equipped with an ambient noise control function (The ANC function distinguishes between the unit's output sound and the ambient noise. The unit's output sound is not detected as noise.) and an automatic level control function that keeps the input signal level constant. It can be mounted in an EIA Standard equipment rack (1 unit size).

■ SPECIFICATIONS

Power Source		110 – 120 V AC, 50/60 Hz
Power Consumption		20 W (300 mA)
Frequency Response		20 – 20,000 Hz, ±1 dB
Sampling Frequency		48 kHz
Dynamic Range		Over 108 dB (IHF-A weighted)
Distortion		Under 0.006%, 1 kHz, +4 dB* input/output (20 – 20,000 Hz BPF)
Input		Sensor input (Ambient noise sensor microphone input) : +4/-48 dB* changeable, 10 kΩ, electronically-balanced, removable terminal block (4 pins), phantom power (+15 V DC, can be turned on or off with Phantom switch) with +15 V DC terminal Input 1,2: +4/-8/-20 dB* changeable, 15 kΩ, electronically-balanced, removable terminal block (3 pins)
Output		Monitor output: +4 dB*, 600 Ω, electronically-balanced, removable terminal block (3 pins) Output 1,2: +4 dB*, 600 Ω, electronically-balanced, removable terminal block (3 pins)
A/D Converter	24 bit	
D/A Converter	24 bit	
Signal Processing		
Automatic Level Control Function	Level meter (4 LED meters), Automatic input signal level control function, Automatic input sensitivity setting function: +4/-8/-20 dB*, Noise gate level setting: -99 to -3 dB	
Ambient Noise Control Function	Level meter (4 LED meters), BGM/Announce level control function, Automatic sensor input reference level measuring function, Sensor input reference level fine adjustment function, Maximum output signal level control: -15 to 0 dB, Minimum output signal level control: -18 to -3 dB, Sample time setting: 10 s, 20 s, 30 s, 1 min, 5 min Gain ratio setting: (Ambient noise: Output signal level) 6:3, 5:3, 4:3, 3:3, 3:4, 3:5, 3:6, Ambient noise measuring frequency setting: 20 – 20,000 Hz, 3 points	
Maximum Output Signal Level Control Function	-12, -6, 0, +4, +6, +12, +18, +24 dB*	
Input Level Indicator	8 LEDs indicator	
Output Level Indicator	8 LEDs indicator	
Other Feature	Phantom power switch (sensor input), Key lock function, Ground lift switch (INPUT 1, INPUT 2), Input/Output bypass function in power off	
Operating Temperature	0°C to +40°C	
Operating Humidity	Under 90% RH (no condensation)	
Finish	Pre-coated steel plate, black, 30% gloss	
Dimensions	482 (W) × 44 (H) × 303 (D) mm	
Weight	3.7 kg	
Accessory	Power cord (2 m)…1, Removable terminal plug (4 pins)…1, Removable terminal plug (3 pins)…5	

Note: Prepare ambient noise sensor microphone separately.

■ APPEARANCE

