

RE5 FAN

- 3 HP+
- Light Weight - 56lbs.
- Compact - 20" x 24"
- Silent Solid State Variable Speed Control
- Compact "C" Stand Spud Mount
- Built in Programmable DMX 512



www.reelfx.com * 5539 Riverton Ave. N Hollywood, CA 91601 * (818) 762-1710

REEL
EFX
INC.

New Features:

- 3 HP+
- Universal Voltage Input 100 – 240 VAC
- Active Power Factor Correction (1.0 pf at Max Load)
- Silent Smart Switching, Eliminates drive noise at low rpm
- Performance Improvements
- Faster Responding Control System
- 33% More Power than its Predecessor “The RE4”
- Improved Active Brake, to stop blades at zero speed
- Eco Friendly RoHs Compliant Construction
- UL/cUL Compliant (Optional)

Specifications:

- Input Ratings
 - * Voltage: 100 - 240 VAC
 - * Current: 21 - 11.6 A
 - * Phase: Single
 - * Max Power: 2800 Watts
 - * Frequency: 50/60 Hz
- Motor: Baldor® Premium Efficient 3-Phase
- Full Speed: 2100 RPM, 39 MPH at 1 yd on 200 - 240 VAC
- Speed Control: Solid State Variable Frequency Drive
 - * Active Silent Smart Switching
 - * Active Power Factor Correction
- DMX Control: USITT Compliant DMX 512 with 5 Pin XLR
- Mounting: Steel Floor Stand with Spud Mount
- Blades: 9 Blades 16” Diameter (41 cm)
- Body Size: 20” x 24” (51 x 61 cm) Rotomolded High Impact Plastic
- Weight: 56 lbs (25.40 kg)
- Grill: Front & Rear Flow Enhancing Impact, Resistant Nylon Grills
- Warranty: 1-Year Parts & Labor



Other Products:



RE2 FAN



DF-50 Diffusion Hazer