



GENERAL INFORMATION

Elegant and clean-lined, Unison Heritage Locking Covers are designed to complement – not to compete with – the aesthetics of any interior environment. Artful but durable, Heritage Locking Covers are engineered to stand up to the daily abuse of busy public areas. A member of the Secure-It family of products, Unison Heritage Locking Covers are designed to prevent unauthorized use of Unison Heritage Button and Fader Stations, while providing protection for the station from accidental damage. Heritage Locking Covers are designed to allow easy access when required while providing visual feedback of the system status through a smoked polycarbonate window.

APPLICATIONS

- Churches
- Hotels
- Convention Centers
- Meeting Rooms
- Schools
- Restaurants

FEATURES

- Secure-It – Decide who has access to the lighting controls, locking out any unwanted actions, while protecting a Heritage Button or Fader station from external damage.
- Designed for use with all Unison Heritage Button, Fader and Keyswitch wall stations

ORDERING INFORMATION

Unison Heritage Sliding Locking Covers

MODEL	DESCRIPTION
SL-1_	1-Gang Flush-mount Sliding Locking Cover
SL-2_	2-Gang Flush-mount Sliding Locking Cover
SL-3_	3-Gang Flush-mount Sliding Locking Cover
SL-4_	4-Gang Flush-mount Sliding Locking Cover
SL-5_	5-Gang Flush-mount Sliding Locking Cover
SL-6_	6-Gang Flush-mount Sliding Locking Cover
SL-7_	7-Gang Flush-mount Sliding Locking Cover

Notes:

Enter color code in __ space provided:

C = Cream (RAL 9001)

I = Ivory (RAL 1015)

G = Gray (RAL 7001)

B = Black (RAL 9004)

W = Signal White (RAL 9003)

Ivory Gray and Signal White are available in single gang configurations only



SPECIFICATIONS

FUNCTIONAL

- For Flush-mount applications
- Mounts to industry standard flush-mount backboxes (by others)
- Accommodates mounting for upward or downward door opening
- Includes integrated locking cylinder
- Maintains functionality of Unison RemoteDirect Infrared remotes

MECHANICAL

- Standard configurations for 1 gang thru 7 gang applications
- Constructed of injection molded, ABS plastic endcaps with extruded aluminum rails in five standard colors, matched to RAL standard colors
- Smoked polycarbonate window with captive mounting
- Integrated key cylinder with two keys
- No visible means of attachment
- Mounts to industry standard back box (by others)
- Accommodates RemoteDirect Infrared remote transmission through polycarbonate window.

PHYSICAL

Unison Heritage Sliding Locking Covers Dimensions*

MODEL	HEIGHT		WIDTH		DEPTH	
	inches	mm	inches	mm	inches	mm
SL-1	6.36	161.5	5.19	131.8	1.32	33.52
SL-2	6.36	161.5	7.33	186.2	1.32	33.52
SL-3	6.36	161.5	9.14	232.2	1.32	33.52
SL-4	6.36	161.5	10.95	278.1	1.32	33.52
SL-5	6.36	161.5	12.76	324.1	1.32	33.52
SL-6	6.36	161.5	14.58	370.3	1.32	33.52
SL-7	6.36	161.5	16.39	416.3	1.32	33.52

Unison Heritage Sliding Locking Covers Weights*

MODEL	WEIGHT		SHIPPING WEIGHT	
	lbs	kgs	lbs	kgs
SL-1	.94	0.4	2.14	1.0
SL-2	1.26	0.6	2.46	1.1
SL-3	1.56	0.7	2.76	1.3
SL-4	1.86	0.8	3.06	1.4
SL-5	2.13	1.0	3.33	1.5
SL-6	2.37	1.1	3.57	1.6
SL-7	2.67	1.2	3.87	1.7

*Weights and dimensions typical



Corporate Headquarters • 3031 Pleasant View Rd, PO Box 620979, Middleton WI 53562 0979 USA • Tel +1 608 831 4116 • Fax +1 608 836 1736

London, UK • Unit 26-28, Victoria Industrial Estate, Victoria Road, London W3 6UU, UK • Tel +44 (0)20 8896 1000 • Fax +44 (0)20 8896 2000

Rome, IT • Via Ennio Quirino Visconti, 11, 00193 Rome, Italy • Tel +39 (06) 32 111 683 • Fax +44 (0) 20 8752 8486

Holzkirchen, DE • Ohmstrasse 3, 83607 Holzkirchen, Germany • Tel +49 (80 24) 47 00-0 • Fax +49 (80 24) 47 00-3 00

Hong Kong • Room 1801, 18/F, Tower 1 Phase 1, Enterprise Square, 9 Sheung Yuet Road, Kowloon Bay, Kowloon, Hong Kong • Tel +852 2799 1220 • Fax +852 2799 9325

Web • www.etcconnect.com • Copyright©2009 ETC. All Rights Reserved. All product information and specifications subject to change. 7181L1004 Rev. A Printed in USA 02/09

Unison® products protected by one or more of the following U.S. Patent Numbers 5,323,088, 5,352,958 and 6,849,943; European Pateten Number 0603333; German Patent Number 69203609; US and International patents pending