

MM-202B Gooseneck Microphone

Key Features

- Ultra slim profile design for podiums, pulpit and lectern applications.
- Proprietary microphone mount design allows 110° up/down and 300° left/right angle adjustments.
- Shock isolation mount design minimizes handling and vibration noise.
- Multi-layered microphone grill minimizes pop noise.
- Can be connected to MJ-53 Condenser Microphone Adaptor and provides with 48V phantom power and used as a desktop gooseneck microphone.
- Unmatched high fidelity sound reproduction.

Related

ACT-7T	Bodypack Transmitter
ACT-30T	Bodypack Transmitter
ACT-50T	Bodypack Transmitter
ACT-70T	Wideband Bodypack Transmitter
ACT-80T	Wideband Digital Miniature Bodypack Transmitter
BC-100	Wireless Boundary Microphone
MD-101	Bodypack Transmitter Holder Base

Technical Specifications

Capsule Module	10mm \emptyset Uni-directional condenser microphone
Frequency Response	50Hz~18kHz
Sensitivity	-46dBV \pm 3dBV/Pa (0dB=1V/Pa)
Maximum SPL	142dB (Typical, 1%THD)
Plug	TA4F 4-pin Connector
Length	370mm / 14.5"
Color	Black
Weight	Approx. 34g / 1.2oz

