



Configuration:

ACFB50U20 3.0 mm² Flat Copper Tape 164 ft. (50 m)

ACFB100U20 3.0 mm² Flat Copper Tape 328 ft. (100 m)

ACFB200U20 3.0 mm² Flat Copper Tape 656 ft. (200 m)

Product Overview:

Ampetronic flat copper tape (cable) is the default choice when installing loop cable under floor coverings such as carpet, wood, laminate, tiles or linoleum. The cable will not be visible under most floor coverings and is generally secured to the floor with Printed Warning Tape that alerts tradespeople, such as carpet fitters to its presence.

The tape can be attached to feeder cables using crimps or soldering and plastic extrusion is available to cover it in high traffic areas. There are three sizes of flat cable available depending on application. The insulating layer of the cable is bonded to the copper for better handling.

Available in lengths of: 50m. (164 ft.), 100 m. (328 ft.), 200 m. (656 ft.)

Highlights:

- Simplifies the installation of loops under floor coverings such as carpet, vinyl, laminate and wood
- Protected by a bonded polyester film
- UL Recognized
- Supplied in 164 ft. (50 m), 328 ft. (100 m) or 656 ft. (200 m) lengths

Includes:

One (1) ACFB50U20 3.0 mm² Flat Copper Tape 164 ft. (50 m)
or
One (1) ACFB100U20 3.0 mm² Flat Copper Tape 328 ft. (100 m)
or
One (1) ACFB200U20 3.0 mm² Flat Copper Tape 656 ft. (200 m)

Product Specification: 3.0 mm ² Flat Copper Tape	
Physical	
Material	Flat Copper covered in bonded polyester film
Length	50 m (164 ft.), 100m (328 ft.), 200m (656 ft.)
Weight	1.0 kg (2.2 lbs.)
Thickness	.15 mm (.0059 in.)
Width	20 mm (.79 in.)
Shipping Weight	1.0 kg (2.2 lbs.)
* Specifications subject to change without notice.	