

COLORISE

RGBALC

Next-Level Color Mixing

Indoor Brilliance

Colorise™ RGBALC is an IP20 rated indoor LED wash fixture with 7x 20W RGBALC 6-in-1 LEDs and exceptional lighting capabilities. It delivers dynamic color mixing and smooth virtual color wheel effects. With its precise 25° beam angle, variable electronic dimming, and eye-catching strobe effects, this fixture offers unparalleled versatility and captivating brilliance. Crafted for indoor performance, it stands as a top choice for any indoor lighting application, from concerts to theatrical productions.

Control & Design

Designed for durability and user-friendly control, the Colorise™ RGBALC is housed in convection-cooled cast aluminum and equipped with locking AC connections. Its OLED menu with touch-sensitive buttons ensures intuitive operation, while dual mounting brackets add mounting flexibility. With flicker-free LEDs, it's perfect for video applications, and its multiple dimming curves and user-customizable effects enhance adaptability, making it a reliable and innovative solution for diverse indoor lighting scenarios.

Luminous Intensity

Beam	2M	2.5M	3M	4M	5M
25°	8,978	6,204	4,322	2,348	1,401



Main Features

- Color mixing via 7x 20W RGBALC 6-in-1 LEDs
- Variable electronic dimming & strobe
- Auto mode and custom macro effects
- Virtual color wheel effects
- Color presets and custom colors
- 2700K to 6500K white presets
- 4x user-selectable dimming curves
- Flicker-free constant-current LED driver
- OLED menu with 4x touch-sensitive buttons
- IP20 rated, suitable for indoor use
- Dual mounting brackets
- Convection cooled cast aluminum housing
- Locking power and 3/5-pin DMX connections



Optical

7x 20W RGBALC 6-in-1 LEDs (100,000 hrs.)
25° beam angle
Flicker-free LEDs



Weight & Dimensions

11.4" x 6.25" x 12.5"
(289 x 158 x 317 mm)
9.7 lbs. (4.4 kg)



Control

Protocol: USITT DMX-512
3/5-pin DMX in/out
6/8/12-channel DMX
4-button menu with OLED display
DMX512, M/S, standalone, auto mode



Power + Current

100-240VAC, 50-60 Hz
Consumption: 112W, 1.48A, PF: .65
PowerCON™ TRUE1-compatible in/out



Warranty + Certifications

2-year limited warranty
cETLus certified