

The Light Source Coupler with Eye Nut



The Mega-Coupler with Eye Nut has a Forged Steel Eye Nut for making rigging connections from a pipe or truss. The Forged Eye Nut is secured to the Mega-Coupler with a 1/2" flathead socket screw with permanent loctite. The Eye Nut rigging connection is 2-3/4" below the pipe and is able to swivel for proper orientation before loading. The Mega-Coupler will fasten from 1-1/4" pipe (1.660" OD) to 2.050" OD truss tube. The Mega-Coupler has our wide wing nut for fastening the clamp to the pipe or tube. Safe Vertical Working Load 1100 Pounds, (500 KG).

Minimum Size

1.25" pipe, 1.66" OD pipe

Maximum Size

1.5" pipe, 1.90" OD pipe, 2" OD truss tube

Working Load Limit

1100 Pounds

Hardware

Forged steel eye nut.
1/2" flathead socket screw with permanent loctite.

Dimensions

2.5" Tall 2" Wide 4" Thick I.D. of 1.2" Wide I.D. of 1.5" Tall The I.D. is pear shaped

Weight

1.3 Pounds

Case Quantities

24

Order Codes

MLMSE Mega-Coupler with Eye Nut, Silver
MLBSE Mega-Coupler with Eye Nut, Black Anodized
MLMSE-SW Mega-Coupler with Eye Nut, Steel Wing Nut, Silver
MLBSE-SW Mega-Coupler with Eye Nut, Steel Wing Nut, Black Anodized
MLWSE Mega-Coupler with Eye Nut, White Powder Coat