



**PRELIMINARY DATA SHEET** 

500W Full Spectrum RGBMA LED Wash



#### **KEY FEATURES**

500W Full Spectrum RGBMA LED Engine

Up to 17,000 Total Lumen Fixture Output @ 6,500K

CRI up to 92

Wide Zoom Range from 10° to 45°

Variable 16-bit Dimming Curve Modes

**CMY Emulation** 

Virtual Color Correction

Green/Magenta Shift

Virtual Gel Swatch Book

The **FUZE WASH 500™** is a powerful automated LED Fresnel wash fixture designed for theater, television, events and a wide array of other precision lighting applications. A High-CRI engine utilizes a 5-color homogenized LED array consisting of Red, Green, Blue, Mint, and Amber sources. The carefully tuned LEDs ensure accurate color reproduction while delivering a powerful output of up to 17,000 lumens and maximum CRI of 92. Virtual color temperature, Magenta / Green adjustment plus CMY emulation provide the designer with immediate access to the impressive LED color array.

The **FUZE WASH 500** is designed for any application where an automated Fresnel fixture with outstanding and impactful colors, a wide zoom range and a soft field is required. An optional indexable ovalizer lens is available for additional beam control.







500W Full Spectrum RGBMA LED Wash

## **SPECIFICATIONS**

#### **SOURCE**

500W 6,500K RGBMA (Red, Green, Blue, Mint, Amber) LED Engine 30,000 Hour Average LED Life\*

\*Test lab conditions. May vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming.

### PHOTOMETRIC DATA

17,000 Total Lumen Fixture Output CRI 92 Zoom Range 10° - 45°

#### **EFFECTS**

Motorized Zoom Optional Indexable Ovalizer Lens Optional Motorized Barn Doors Variable 16-bit Dimming Curve Modes High Speed Electronic Shutter and Strobe Pan 540°/630° Tilt 228°/180°

#### **COLOR**

RGBMA Color Array CMY and RGB Emulation Virtual Color Correction 2400K - 8500K Green/Magenta Shift Virtual Gel Swatch Book

#### **CONTROL / CONNECTIONS**

6 DMX Channel Modes (RGBMA 21/30) (CMY 17/24) (RGB 20 / 26)
16-bit Pan, Tilt, and Dimming Control DMX Adjustable LED Frequency DMX, RDM, E-FLY Wireless, Art-Net, sACN Protocol Support
4 Button Touch Control Panel Full Color 180° Reversible LCD Menu Display Locking 5pin XLR Connector In/Out Locking RJ45 Ethernet Connector In/Out Locking IP65 Power Connector In/Out USB Connection (Firmware Updates)

#### SIZE / WEIGHT

Length: 16.0" (408mm) Width: 10.1" (256mm) Vertical Height: 23.2" (590mm) Center Spacing: 23.6" (600mm) Weight: 40.8 lbs. (18.5kg)

### **ELECTRICAL / THERMAL**

AC 100-240V - 50/60Hz Max Power Consumption 609W 14°F to 113°F (-10°C to 45°C) BTU/hr (+/- 10%) 2151.71

#### APPROVALS / RATINGS

CE | cETLus | IP20 | FCC















500W Full Spectrum RGBMA LED Wash

ORDER CODE	ITEM
FUZ567 (US) / 1521000387 (EU)	Elation Fuze Wash 500
FUZ567WH (US) / 1521000412 (EU)	Elation Fuze Wash 500 WH
TRIGGER CLAMP	Heavy Duty Wrap Around Hook Style Clamp
SIP126	5 ft. (1.5m) IP65 Twist Lock Power Link Cable
AC5PDMX5PRO	5 ft. (1.5m) 5pin PRO DMX Cable
	Additional Cable Lengths Available
8030500064	Beam Shaper
8050000652	Motorized Barn Doors









500W Full Spectrum RGBMA LED Wash

## **DIMENSIONS**











