

# Lighting Fixtures

## FXLE1530W

### Dimmable Warm White LED Ellipsoidal



- Body Color: Black
- Beam Spreads: 19°, 26°, 36°, or 50°
- LED Array: 150 watt \ 3000K
- Illuminance: 52,084 lux at one meter (19°)
- CRI: 93
- CQS: 93
- Power Draw: 1.8 amps (max)
- DMX modes: 1 or 2 channels
- IP Rating: 20
- Weight: 19 lbs.

#### SPECIFICATIONS

Control System: DMX512 or Stand Alone  
 DMX connections: 3 pin XLR I/O  
 Power input: 100-230VAC  
 Power connector: 250VAC / 20amp turn and lock for I/O  
 Body material: Rugged all steel construction

Cooling: Quiet smart fan with auto shut off  
 Optics: Dual glass lenses for enhanced optics  
 Reflector: Glass  
 Dimensions: 28"L x 13.5"W x 20"H (with yoke)

	10'			20'			30'		
	Beam Dia.	foot candle	lux	Beam Dia.	foot candle	lux	Beam Dia.	foot candle	lux
FXLE1530W									
19°	3	748	7940	6	186	1970	9	83	900
26°	3.75	510	5570	7.5	125	1342	11.5	57	623
36°	6	210	2320	12	56	605	19	26	282
50°	7.25	165	1775	14	43	462	23	19	207

\*All models come standard with gel frame, gobo holder, five foot DMX cable, power cord, and power out connector to connect with next fixture inline.