

# Lighting Fixtures



## FXLE30C4N

Dimmable Four Color (RGBW) LED Ellipsoidal

- Body Color: Black
- Beam Spreads: 19°, 26°, or 36°
- LED Array: 300 watt \ RGBW
- Illuminance: 120,253 lux at one meter (19°)
- CRI: 93
- CQS: 92
- Power Draw: 2.8 amps (max)
- DMX Modes: 4 or 9 channels
- IP Rating: 20
- Weight: 23 lbs.

### SPECIFICATIONS

Control System: DMX512 or Stand Alone  
 DMX connections: 3 pin XLR I/O  
 Power input: 100-230VAC  
 Power connector: 250VAC/20amp turn and lock for I/O  
 Body material: Rugged all steel construction

Cooling: Quiet smart fan with auto shut off  
 Optics: Dual glass lenses for enhanced optics  
 Reflector: Glass  
 Dimensions: 28"L x 13.5"W x 20"H (with yoke)

	10'			20'			30'		
	Beam Dia.	foot candle	lux	Beam Dia.	foot candle	lux	Beam Dia.	foot candle	lux
<b>FXLE30C4N19</b>									
R	3.3	294	3050	6.6	64	682	10.5	27	455
G	3.3	302	3210	6.6	70	758	10.5	30	508
B	3.3	492	5,200	6.6	113	1226	10.5	50	840
W	3.3	550	5950	6.6	136	1458	10.5	57	966
All	3.3	1535	16,120	6.6	366	3920	10.5	158	2580
<b>FXLE30C4N26</b>									
R	4.7	160	1810	9.4	40	443	14.2	18	196
G	4.7	186	1995	9.4	45	489	14.2	21	228
B	4.7	300	3,160	9.4	76	824	14.2	34	372
W	4.7	340	3720	9.4	86	936	14.2	39	427
All	4.7	950	10,120	9.4	237	2520	14.2	105	1168
<b>FXLE30C4N36</b>									
R	6.5	89	960	12.9	23	255	19.5	11	121
G	6.5	99	1100	12.9	27	294	19.5	12	134
B	6.5	170	1,835	12.9	45	486	19.5	20	223
W	6.5	192	2050	12.9	51	554	19.5	28	309
All	6.5	532	5,590	12.9	140	1530	19.5	77	820

\*All models come standard with gel frame, gobo holder, five foot DMX cable, power cord, and power out connector to connect with next fixture inline.