



[www.galaxyaudio.com](http://www.galaxyaudio.com)

### **THREE YEAR LIMITED WARRANTY**

WARRANTY Information can be viewed online at  
<https://www.galaxyaudio.com/support/warranty>



[www.galaxyaudio.com/support/warranty](http://www.galaxyaudio.com/support/warranty)

# **GT-S240WP**

1-800-369-7768 [www.galaxyaudio.com](http://www.galaxyaudio.com)

Specifications in this manual are subject to change without notice.

© Copyright Galaxy Audio 2019

Printed in China

V20190326



## **GT-S240WP**

**Waterproof Headset Mic System**

## **USER'S MANUAL**



**MAKERS OF THE ORIGINAL  
HOT SPOT PERSONAL MONITOR**



## GT-S24OWP

## Instructions

1. Put the receiver into the 1/8" (3.5 mm) Mic input of an amplifier, powered speaker, or other audio device or use the included 1/4" (6.5 mm) adapter for 1/4" inputs. For Apple or Android phones, use the included phone adapter cables.



2. Attach the Transmitter to the Headset with the cable and secure the cable to the cable clip.



3. Attach the included Belt Clip onto the Transmitter.



4. On the Receiver, move the Power switch to On. The LED will begin flashing.



5. On the Transmitter, move the Power switch to On. The LED will briefly flash until the Transmitter and Receiver automatically pair. The LED will then remain on.



6. Adjust the volume to a suitable level. It is ready for use.



## Caution

The LED will turn red when power is low, and will turn off when less than 10%. The LED will also turn red when charging.

Store in a dry location away from moisture. Avoid excessive heat.

For repair services, please contact Galaxy Audio. Do not attempt open or repair it. Doing so will void warranty.



Transmitter



Headset



Receiver

**System Specifications:**

Frequency Range: 2.4GHz Frequency Hopping

Frequency Response: 20Hz-20KHz

Pairing: Auto-Match

**Headset Microphone:**

Polar Pattern: Omni-Directional

Sensitivity:  $-40 \pm 2$ dBV/Pa

Frequency Response: 50Hz-16kHz

Max SPL: 120dB

Signal to Noise Ratio:  $>63$ dB

Impedance:  $\leq 2.2$ k $\Omega$

Element Diameter: 2.7mm

Element Type: Back Electret Condenser

**Transmitter:**

Controls: On-Off Power Switch, Volume Control

Battery: Lithium-Ion Rechargeable

Input: Mini USB Charging

Indicators: Power and Pairing LED

**Receiver:**

Controls: On-Off Power switch

Battery: Lithium Ion

Input: Mini USB charging

Output: 3.5mm stereo output plug

Indicators: Power and Pairing LED

**Included Accessories:**

Detachable Belt Clip

Cell Phone Adapter Cables (Red for most Android, Black for most Apple)

1/8 inch to 1/4 inch Adapter

USB Charging Cable

19.7 inch Female to Male Extension Cable

Windscreen