

Compact Yet Captivating

Built to impress, the HotBox™ 5 RGBAW offers phenomenal color mixing, advanced electronics, and a huge amount of light output that can impress any crowd. Just like our larger RokBox™ 5 fixtures, the HotBox™ 5 offers 5-in-1 LEDs, a rock-solid aluminum casing, and all the same great features in a compact package.

HotBox™ 5 RGBAW fixtures are equipped with 7x 15W 5-in-1 LEDs, and feature 4/5/9 or 10 user selectable DMX channel modes. Users have full control of color mixing, 31 built-in programs, 5 user-selectable 32-bit dimming modes, and HSV color mixing ability in 4-channel mode.

It's built-in 4-button LED control panel allows total control over the fixture including master/slave settings, sound active mode, built-in programs, auto mode, custom color mixing, and user adjustable fade/strobe effects. It also comes equipped with industry standard powerCON® compatible power input/output & 3-pin DMX connections.

Users can take full advantage of Blizzard's wiCICLE® wireless DMX system without the need for external power thanks to its wiCICLE enabled DMX jacks. An innovative design provides power to the system directly from the DMX input, meaning even fewer cords and less setup time.

These fixtures are ETL listed, and they are backed by Blizzard's 2-year limited warranty!

Luminous Intensity:

		Green	Blue	Amber	White	All
. 1m	2,600	2,710	2,920	1,280	3,460	11,490
2m	800	780	850	410	1,010	3,260









Main Features

- RGBAW color mixing via 7x 15W 5-in-1 LEDs
- 5 user-selectable 32-bit dimming curves
- Variable electronic dimming & strobe
- Built-in color & chase macros via DMX
- Built-in automated programs via master/slave
- Built-in sound active programs
- Super-quiet variable-speed internal fan cooling
- Dual mounting brackets for positioning flexibility
- Flicker-free constant-current 400hz LED driver
- 3-pin male input and 3-pin female output
- PowerCON® compatible AC power In/Out connectors



Optical

Light source: 7x 15W 5-in-1 LEDs 100,000 hours

Beam Angle: 25 degree optics standard, 26 degree beam, 30 degree field



Weight & Dimensions

5" L x 4" W x 5" H (127 x 101.6 x 127mm)

3.5 lbs (1.6 kg)



Control

Protocol: USITT DMX-512

DMX Channels: 4/5/9/10

Operating Modes:

Standalone, M/S, Sound Active, Color Preset



Power + Current

Operating Voltage: 100-250VAC, 40-60 Hertz

Fuse: 2A 250V

Power Consumption: 58W, .83A

Power Factor .56



Warranty

2-year limited warranty













