

IR-842PMU-AM

INFRARED AUDIO SYSTEM MAIN UNIT



The IR-842PMU is a compact, portable infrared classroom soundfield system, designed for use in conjunction with TOA's IR-200M (hand-held), IR-300 (hands-free), or IR-310 (hands-free) infrared wireless microphones, featuring high sensitivity and clear sound.

Key features

Bluetooth® functionality

Specifications

Power Source	100 - 240 V AC, 50/60 Hz (use of the supplied AC adapter)
Power Consumption	60 W (120 W max. including sub unit speaker output)
Rated Output	40 W (80 W max. including sub unit speaker output)
Frequency Response	20 - 20 kHz, 3 dB
Amplification System	Class D Amplifier
Total Harmonic Distortion	0.1 % (LPF 20 kHz)
Speaker Component	5.5"full range speaker driver
Infrared Wireless Receiver	
Wavelength	850 nm
Carrier Frequency	Teacher (CH-A): 3.100 MHz Student(CH-B): 3.350 MHz
Communication Area	Approx. 15 m (49.21 ft) in a space without any obstacle and visible between the infrared microphone and receiver
Reception Angle	120 Degrees
Connetion Terminal For External IR Receiver RJ-45	
Audio Input	MIC: -42 dBV, 2.2 k Ω , electronic balanced, female XLR connector AUX: -10 dBV, 10 k Ω , stereo pair, unbalanced, headphone jack Bluetooth input: Ver. 5.0, Max. 10m
Audio Output	Sub unit speaker OUT: 23.8 dBV, unbalanced, lever terminal AUX OUT: -10 dBV, 10 k Ω , stereo pair, unbalanced, headphone jack
Signal to Noise Ratio	Over 70 dB (A weighted)
Phantom Power	+24 VDC, switchable, MIC input
Compliance/Certifications	FCC, ICES
Connection Terminal	RJ-45, 2 Way Spring Speaker Terminal Clip
Indicators	Power(green) x 1, IR CH-A(green) x 1, IR-B(green) x 1, IR CH-A Priority(red) x 1, Bluetooth®(blue) x 1, Phantome power(green) x 1
LED Indicator	Power, IR Transmitters, Bluetooth®, XLR, Bluetooth®, and Phantom Power
Operation	IR CH-A volume control, IR CH-B volume control, MIC volume control AUX IN volume control, AUX OUT volume control, Bluetooth® volume control
Operating Temperature	0 °C to +40 °C (32 °F to 104 °F)
Operating Humidity	Under 90 % RH (no condensation)
Finish	Enclosure: MDF, white, paint Punched net: Surface-treated steel plate, white, paint
Dimensions	218 (W) x 339.6 (H) x 254 (D) mm (8.60" x 13.37" x 9.99")
Weight	4.97 kg (10.96 lbs)
Included Accessories	AC Power Adapter x 1, Wall Mounting Bracket x 1

*The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by TOA corporation is under license. Other trademarks and trade names are those of their respective owners.