

### Wireless XLR Bluetooth® 5 Receiver

The JIB/BT5R is a lightweight, compact, portable XLR Bluetooth® 5 receiver that allows a user to transmit quality Bluetooth® audio wirelessly from a smartphone to an active speaker or mixing console. The receiver offers a practical, straightforward audio solution for venues that require a quick wireless setup. Just pair the receiver to a Bluetooth® enabled device such as a smartphone and plug it into an active speaker or mixing console. Using the JIB/BT5R eliminates cable clutter for a clean, hassle free setup. The rechargeable receiver enlists an internal 3.7V Lithium battery and comes standard with a micro USB charging cable that can be plugged into a computer or A/C adapter to charge. For a more permanent mixer installation, the JIB/BT5R can stay plugged in for a continuous power source.

The JIB/BT5R can also be used for a number of other audio streaming applications including dance studios, aerobics classes, school and gym classes, house of worship, karaoke, weddings, and many more.

#### JIB/BT5R

- Bluetooth 5 Receiver with over 300 ft. range (100 meters)
- Transmit Audio from a Bluetooth® Source to an Active Speaker or Mixer
- Single/Dual Receivers for Mono or Stereo Playback
- Lightweight, Compact, & Portable
- Micro USB Rechargeable

 **Bluetooth® 5**



### Dual Receiver Stereo Playback System

## JIB/BT5RS

The JIB/BT5RS system comes with two receivers to create a stereo link. The two receivers pair together to turn the audio transmission into a stereo playback to better fill a room with more sound.

#### JIB/BT5RS

- Two included Bluetooth 5 Receivers for Stereo Playback
- Bluetooth 5 Receiver with 328 ft. range (100 meters)
- Transmit Audio from a Bluetooth® Source to an Active Speaker or Mixer
- Single/Dual Receivers for Mono or Stereo Playback
- Lightweight, Compact, & Portable
- Micro USB Rechargeable



# JACKS in the BOX

**JIB/BT5R**

## Specifications:

### JIB/BT5R

**Bluetooth® Version:** V5.0

**Frequency Range:** 2.4GHz - 2.48GHz

**Input Connector:** Micro USB Charging Input

**Output Connector:** XLR/M

**Controls:** Power, PAD Switch, Bluetooth Pair/Stereo-Link Button

**Indicators:** Charging LED, Stereo-Link/Pair LED

**Sensitivity:** -80dBm < +/-0.1% BER

**Signal to Noise:** >75dB

**Total Harmonic Distortion:** <0.1%

**Operating Range:** Under Typical Conditions over 300' (100 m)

Note: actual range depends on RF signal absorption, reflection, interference, and battery characteristics

**Operating Temperature:** Range -40° F to 176° F (-40 C° to +80 C°)

Note: battery characteristics may limit this range

**Dimensions:** 4.9" x 1.32" x 1.1"

(124 x 33.4 x 27.5 mm)(HxWxD)

**Weight:** 3.35 oz (95 g)

**Power Requirements:** Internal 3.7V Rechargeable

Lithium Battery / Power Supply

**Battery Operation:** About 10 hours

**Included Accessories:** Micro USB charging cable

 **Bluetooth® 5**  
**JIB/BT5R Receiver**



TOP CHARGING INPUT VIEW



BOTTOM XLR INPUT VIEW



FRONT VIEW



BACK VIEW  
0.72" (18.29 mm)



SUPERIOR SOUND FOR YOU



Specifications subject to change without notice.

601 E. Pawnee Wichita, KS 67211 316. 263.2852 FAX 316.263.0642 [www.galaxyaudio.com](http://www.galaxyaudio.com)

Distributed in Canada by ADIpro.ca 1275 Newton, unit 6 Boucherville, QC J4B 5H2 Canada  
450.449.8177 FAX 450.449.8180

V20221006