

2in1 Color  
White

	10'			20'			25'		
	Beam Diameter (WxH)	foot-candle	lux	Beam Diameter (WxH)	foot-candle	lux	Beam Diameter (WxH)	foot-candle	lux
<b>FXLD618FRP2I25°</b>									
WW	4	21.8	234	6	6	65	7.5	4	43
CW	4	37.5	405	6	9.7	105	7.5	6.4	69
ALL Colors	4	58.2	623	6	15	164	7.5	9.9	106.5

5in1 Color  
Flat Round Par

	10'			20'			30'		
	Beam Diameter (WxH)	foot-candle	lux	Beam Diameter (WxH)	foot-candle	lux	Beam Diameter (WxH)	foot-candle	lux
<b>FXLD1218FRP5I45°</b>									
Red	5	14.5	159	8	3.5	38	12	2.3	23
Green	5	69	751	8	18.2	198	12	11.6	124
Blue	5	35	388	8	9.8	105	12	6.4	69
White	5	43	495	8	12	129	12	7.8	84
Amber	5	13.8	138	8	3.5	39	12	2.2	24
ALL Colors	5	166	1780	8	42	474	12	28.5	310

	10'			20'			25'		
	Beam Diameter (WxH)	foot-candle	lux	Beam Diameter (WxH)	foot-candle	lux	Beam Diameter (WxH)	foot-candle	lux
<b>FXLD127FRP5I25°</b>	3.5	210	2250	6	52	557	8	34	358

6in1 Color  
Flat Round Par

	10'			20'			25'		
	Beam Diameter (WxH)	foot-candle	lux	Beam Diameter (WxH)	foot-candle	lux	Beam Diameter (WxH)	foot-candle	lux
<b>FXLD157FRP6I25°</b>	4	180	1957	6	47	503	8	31	336

Bars

	5'			10'			20'		
	Beam Diameter	foot-candle	lux	Beam Diameter	foot-candle	lux	Beam Diameter	foot-candle	lux
<b>FXLD2512B5I60°</b>									
Red	3x3	11.2	117	6x6	3.9	50	12x12	1.3	14
Green	3x3	44.9	482	6x6	16.2	174	12x12	4.4	47
Blue	3x3	69.5	639	6x6	22	226	12x12	5.6	60
White	3x3	45.3	487	6x6	16.2	175	12x12	4.4	48
Amber	3x3	13.7	142	6x6	5.9	64	12x12	1.6	18
ALL Colors	3x3	168.7	1820	6x6	60.9	657	12x12	16.3	176

LED Ellipsoidal

	10'			20'			30'		
	Beam Diameter	foot-candle	lux	Beam Diameter	foot-candle	lux	Beam Diameter	foot-candle	lux
<b>FXLE1260W</b>									
19°	3'	1170	12,390	7'	280	3050	10'	117	1275
26°	4.5'	774	8300	9.5'	184	1920	14.5'	81	879
36°	6'	514	5500	12.5'	130	1390	19'	55	615
50°	10'	257	2780	19'	65	710	-	-	-
<b>FXLE1232W</b>									
19°	3'	972	10450	7'	224	2410	10'	102	1130
26°	4.5'	658	7120	9.5'	149	1620	14.5'	70	770
36°	6'	437	4520	12.5'	105	1130	19'	49	540
50°	10'	219	2360	19'	51	565	-	-	-
<b>FXLE1530W</b>									
19°	3	748	7940	6	186	1970	9	83	900
26°	3.75	510	5570	7.5	125	1342	11.5	57	623
36°	6	210	2320	12	56	605	19	26	282
50°	7.25	165	1775	14	43	462	23	19	207
<b>FXLE3030W</b>									
19°	2.5'	2150	23200	5'	537.5	5800	7.5'	239	2578
26°	4.75'	1039	10960	9'	279	2950	13.5'	125	1345
36°	6.33'	533	5740	12.6'	143	1545	19'	65.4	704
50°	9'	279	3000	18'	75	807	27'	34	368
<b>FXLE17C4N19</b>									
R	2.33'	68	752	4.5'	13.2	164	7'	6	68
G	2.33'	275	2920	4.5'	67	721	7'	28.6	311
B	2.33'	499	5410	4.5'	121.6	1299	7'	52	556
W	2.33'	368	3960	4.5'	90	960	7'	38.2	416
All	2.33'	1195	12700	4.5'	282	3040	7'	124.3	1278
<b>FXLE17C4N26</b>									
R	3.33'	30.5	329	6.5'	7.5	82	10.5'	3.1	35
G	3.33'	127.5	1366	6.5'	32.9	357	10.5'	14.4	154
B	3.33'	225	2410	6.5'	58.6	636	10.5'	25.3	279
W	3.33'	169.5	1790	6.5'	44.2	478	10.5'	19	205
All	3.33'	528	5,650	6.5'	141.3	1534	10.5'	61.8	659
<b>FXLE17C4N36</b>									
R	4.5'	17.8	194	9'	4.5	51	15.5'	2	22
G	4.5'	77.8	839	9'	20.5	221	15.5'	9.4	101
B	4.5'	137.4	1,500	9'	36	388	15.5'	16.5	180
W	4.5'	104.5	1115	9'	27.2	292	15.5'	12.5	134
All	4.5'	324	3,500	9'	88.4	944	15.5'	40.5	433
<b>FXLE30C4N19</b>									
R	3.3	294	3050	6.6	64	682	10.5	27	455
G	3.3	302	3210	6.6	70	758	10.5	30	508
B	3.3	492	5,200	6.6	113	1226	10.5	50	840
W	3.3	550	5950	6.6	136	1458	10.5	57	966
All	3.3	1535	16,120	6.6	366	3920	10.5	158	2580
<b>FXLE30C4N26</b>									
R	4.7	160	1810	9.4	40	443	14.2	18	196
G	4.7	186	1995	9.4	45	489	14.2	21	228
B	4.7	300	3,160	9.4	76	824	14.2	34	372
W	4.7	340	3720	9.4	86	936	14.2	39	427
All	4.7	950	10,120	9.4	237	2520	14.2	105	1168

FXLE30C4N36									
R	6.5	89	960	12.9	23	255	19.5	11	121
G	6.5	99	1100	12.9	27	294	19.5	12	134
B	6.5	170	1,835	12.9	45	486	19.5	20	223
W	6.5	192	2050	12.9	51	554	19.5	28	309
All	6.5	532	5,590	12.9	140	1530	19.5	77	820