



Configuration:

LP-4VP-072-01 Assistive Listening DSP Value Package (72 MHz) (North America)

Product Overview:

Start your assistive listening setup affordably with the LP-4VP-072 Assistive Listening DSP Value Package. Meeting basic assistive listening needs for houses of worship or private gathering spaces, the LP-4VP-072 includes our LT-803 stationary transmitter, four LR-3200-072 receivers, a 90-degree helical antenna, earbuds, and a signage kit.

Simply add two neck loops to meet ADA compliance for a room with capacity of up to 100 people.

Highlights:

- Economical price – backed by Listen’s exceptional service and support
- Three channels – makes it simple to install, manage and use
- Reliable clear sound quality – 62 dB SNR
- 30-day no-obligation demonstrations available

Includes:

- One (1) LT-803-072 Stationary 3-Channel RF Transmitter (72 MHz)
- One (1) LA-123 90° Helical Antenna (72 MHz)
- Four (4) LR-3200-072 RF Receiver (72 MHz)
- Four (4) LA-161 Single Ear Bud
- One (1) LA-304 Assistive Listening Notification Signage Kit
- One (1) LA-423 4-Port USB Charger

Product Specification: Assistive Listening DSP Value Package (72 MHz)	
Audio	
Frequency Response	50 Hz - 15 kHz (±3 dB)
Signal-to-Noise Ratio	62 dB (A Weighted)
Distortion	1% total harmonic distortion (THD) at 80% deviation
RF	
Number of Channels	Three (3) Wide Band - (A) 72.100, (E) 72.900, (H) 75.900
Transmission Range	600 ft. (182.88 m) (with LA-123 antenna)

Product Specification: Assistive Listening DSP Value Package (72 MHz)	
Physical	
Shipping Weight	5.8 lbs. (2.6 kg)
Dimensions (H x W x D)	Box Dimensions: 18 x 12.25 x 3 in. (45.72 x 31.12 x 7.62 cm)
Environmental	
Temperature - Operation	-10 °C (14 °F) to +40 °C (104 °F)
Temperature - Storage	-20 °C (-4 °F) to +50 °C (122 °F)
Relative Humidity	0 to 95% relative humidity, non-condensing
Compliance	
Standards	FCC Part 15 Class B, Industry Canada ICES-3 (B), RoHS