



Configuration:

LS-57-216 Listen iDSP Advanced Level II Stationary RF System (216 MHz)

Product Overview:

The LS-57 Advanced Level II Stationary RF System offers venues a clear, reliable RF signal from our LT-800-216 216 MHz transmitter, and four (4) LR-5200-216 Advanced iDSP receivers ensure the best possible listening experience for customers, clients, visitors, and more.

Perfect for spaces with a capacity of up to 100 people, the LR-5200-216 receiver offers listeners exceptional audio performance thanks to having 20 dB less hiss than other RF receivers on the market. Each unit gives listeners the choice of multiple channels, ideal for venues where language interpretation or alternate/separate audio streams are needed. The rechargeable Lithium-ion battery in each receiver offers long life and significant cost savings over the life of each unit, and they fully recharge within 2.5 hours.

The included universal antenna and universal rack mounting kit make the LS-57 an adaptable, flexible solution by allowing you to incorporate it into nearly any permanent audio setup. The system also includes universal ear speakers, neck loops/lanyards, a 4-port USB charger, and the assistive listening notification signage kit needed to meet the needs of your customers and ensure your venue’s compliance at the same time.

Highlights:

- Advanced-level 216 MHz RF system with transmitter and four LR-5200-216 advanced iDSP receivers
- LT-800-216 transmitter, universal antenna kit, and rack mounting kit for installing the system in any permanent audio setup
- Lithium-ion rechargeable batteries in each receiver for long service and added affordability
- Includes four universal ear speakers and two integrated neck loops/lanyards
- Four-port USB charger, compliance signage, and RCA cable also included for immediate set up

Includes:

One (1) LT-800-216-01 Stationary RF Transmitter (216 MHz) One (1) LA-122 Universal Antenna Kit (72 MHz and 216 MHz) One (1) LA-326 Universal Rack Mounting Kit Four (4) LR-5200-216 Advanced Intelligent DSP RF Receiver (216 MHz) Four (4) LA-401 Universal Ear Speaker Two (2) LA-430 Intelligent Earphone/Neck Loop Lanyard One (1) LA-423 4-Port USB Charger One (1) LPT-A107-B Dual RCA to Dual RCA Cable 2 m (6.6 ft.) One (1) LA-304 Assistive Listening Notification Signage Kit

Product Specification: Listen iDSP Advanced Level II Stationary RF System (216 MHz)	
Physical	
Shipping Weight	19.0 lbs. (8.62 kg)