



**Configuration:**

LT-800-216-01-D Stationary RF Transmitter  
 (216 MHz) (Dante)

**Product Overview:**

Offering outstanding audio clarity, digital signal strength, and 57 selectable channels, the LT-800-216 is a perfect RF transmitter choice for a wide range of applications and is Dante compatible through the use of the LA-465 Dante adapter. Dante input or universal analog inputs allow for the use of nearly any audio source including mixers, microphones, MP3 players, and more. Connected to your main audio system, the LT-800-216 broadcasts strong, reliable audio to both belt pack receivers and stationary receivers, ideal for providing listeners with the best possible assistive listening experience.

**Highlights:**

- Look & Listen (TM) LCD display for quick channel, programming, and channel lock status information
- Balanced and unbalanced audio inputs allow for use with any audio source
- Dante adapter enabled
- Built-in auto processor optimizes audio (voice or music) prior to transmission
- 57 available, selectable channels
- VU level meter and test tone for simple installation and set up
- 30-day, no-obligation demonstration available for your venue or business

**Includes:**

- One (1) LT-800-216-01 Stationary Transmitter (216 MHz)
- One (1) LA-465 Dante 1 Channel Output XLR Adapter (POE required)
- One (1) LA-207 12 VDC Replacement Power Supply for LT-800
- One (1) Quick Reference Card

Product Specification: Stationary RF Transmitter (216 MHz) (Dante)	
Audio	
Frequency Response	50 Hz - 15 kHz (±3 dB)
Signal-to-Noise Ratio	SQ enabled 70 dB, SQ disabled 50 dB
Audio Input 1	Rear panel, one (1) Female XLR or 1/4 in combo connector, balanced, 0 / -55 dBu (line/mic) nominal input level adjustable, -30 / +21 dBu (line/mic) maximum input level, impedance 20k / 1k ohm (line/mic), phantom power +12 VDC
Audio Input 2	Rear panel, two (2) phono connectors, unbalanced, -10 / +10 dBu nominal input level adjustable, +30 dBu maximum, impedance 100k ohm
Audio Processing	Compression can be turned on/off, slope internally adjustable from 1:1 to 4:1, default 2:1
Contour	Cuts and boosts frequencies above 5 kHz
Distortion	< 2% total harmonic distortion (THD) at 80% deviation
Audio Output	Input 1 and input 2, mixed output (rear panel), two (2) phono connectors, unbalanced, -10 dBu nominal output level, +15 dBu maximum, impedance 10 ohm

Product Specification: Stationary RF Transmitter (216 MHz) (Dante)	
Headphone Output	Front panel, one (1) 3.5 mm (0.14 in.) stereo connector, unbalanced, adjustable output level, +3 dBu maximum, impedance 10 ohm
<b>Controls</b>	
User Controls	Front Panel: Power, test tone on/off, channel up/down, input levels, mix level, contour, monitor volume control Rear Panel: Input 1 Level, (Line, Mic, Mic-Phantom Power), Input 2 level (-10 / +10 dBu), RF power level (low, mid, high)
Internal Adjustments	Compression ratio for audio processor
Programming	SQ on/off, process on/off, channel lock
<b>Indicators</b>	
LCD	Channel designation, lock status, RF power level, programming (front panel)
Audio Input Status LEDs	Indicates Input 1, Input 2, and Mix audio levels; 10 segment LED's (8 green, 2 red)
Processing	Indicated by a green LED when on (front panel)
Test Tone	Red LED illuminates when test tone is enabled
RF Power	Indicated on the LCD (low, mid, high)
<b>RF</b>	
Frequency Range	216.0125 - 216.9875 MHz
Number of Channels	19 wide band, 38 narrow band
Frequency Accuracy	± .005% stability +32° to +122 °F (0° to +50 °C)
Antenna Type	Various antennas available
Transmitter Stability	50 PPM
Transmission Range	Up to 3,000 ft. (914 m)
Antenna Connector	BNC, 50 Ohms (Use RG-58 < 50 ft or RG-8 > 50 ft)
Output Power	100 mW (max allowed by FCC)
Number of Simultaneous Transmitters	Up to 5
<b>Power</b>	
Power Supply	In line power supply, Listen part number LA-207 (Line cord is determined by the each Country's AC power standards)
Power Supply Input	100-240 VAC, 50-60 Hz, 0.4 A
Power Supply Output	12 VDC, 1.3 A, 15.6 W
Power Supply Connector	0.02 in (5.0 mm) OD, 0.01 in. (2.5 mm) ID, barrel type
Compliance	UL, CE, GS, TÜV, RoHS
<b>Physical</b>	
Width	8.50 in. (21.5 cm)
Height	1.75 in. (4.5 cm)
Depth	9.13 in. (23 cm)
Color	Dark Grey with white silk screening
Unit Weight with Power Supply	3.5 lbs. (1.6 kg)
Shipping Weight	6.0 lbs. (2.7 kg)
Rack Mounting	One (1) rack space height, 1/2 rack space wide. One (1) or two (2) transmitters

Product Specification: Stationary RF Transmitter (216 MHz) (Dante)	
	can be mounted in one rack space, optional rack mount (LA-326)
Weight	2.6 lbs. (1.2 kg)
<b>Environmental</b>	
Temperature - Operation	-10 °C (14 °F) to +40 °C (104 °F)
Temperature - Storage	-20 °C (-4 °F) to +50 °C (122 °F)
Relative Humidity	0 to 95% relative humidity, non condensing
<b>Compliance</b>	
Safety	RoHS
RF	FCC Part 15, Part 90, Industry Canada