

M-44DT-AM

DANTE AUDIO INTERFACE



A Dante audio interface with 4 inputs and 4 outputs that seamlessly connects amplifiers, mixers, digital microphones, and other devices on a Dante network. It can be mounted in an EIA standard equipment rack with the rack mounting panel MB-M44DT (optional).

Key features

- 4 inputs
- 4 outputs
- individual gain controls
- rack mountable

Specifications

| | |
|---------------------------|--|
| Power Source | 100 - 240 V AC, 50/60 Hz (use of the supplied AC adapter) |
| Current Consumption | 10W |
| Input | Input 1-4: -50 - 0 dBV, 4.4 k Ω , electronic balanced, removable terminal block |
| Output | Output 1-4: 0 dBV, 10 k Ω , electronic balanced, removable terminal block |
| Frequency Response | 20 - 20,000 Hz, \pm 3 dB |
| Total Harmonic Distortion | 0.01% (LPF 20 kHz) |
| Network Protocol | 100Mbps, RM II |
| Operating Temperature | 0°C to +40°C (32°F to 104°F) |
| Operating Humidity | 90% RH or less (no condensation) |
| Finish | Panel: Aluminum, black, alumite Case: Surface-treated steel plate, black, paint |
| Dimensions | 130 (W) X 44 (H) X 161 (D) mm (5.12" X 1.73" X 6.34") |
| Weight | 0.81 kg (1.79 lbs) |
| Included Accessories | AC Power adpopter x1, Removable terminal plug (6 pins) x4 |

Product rear image



Dimensions