


The Light Source

Mega-Truss Pick for Threaded Rod Installations

12" Threaded Rod Truss Pick pictured above -



Two 1" x 2" x 15" 6061T-6 aluminum bars CNC machined with pockets to support one piece of 12" truss. The Mega-Truss Pick will suspend up to one ton of truss load when the Mega-Truss Pick is suspended by two customer supplied 1/2" threaded rods, or two 1/2" forged steel shoulder eyebolts fastened through the outside support holes. All of the holes are through holes without threading. Secure the threaded rod with a nut and washers above and use a nyloc nuts with a USS washer below the truss pick.

Rigging from only the center hole de-rates the Threaded Rod Truss Pick to 250 pounds capacity.

Priced per pair.

Available in 12", 18", 20.5" sizes.
11.4375" for Global Truss.

Working Load Limit

2000 lbs with two outside 1/2" threaded rods

Dimensions

1" x 2" x 21" (18 inch) 1" x 2" x 15" (12 inch)

Weight

12" - 5 lbs. 18" - 7 lbs.

Case Quantities

each pair

Order Codes

MTPTR12B Mega-Truss Pick 12 inch for Threaded Rod Installations, Black Anodized
MTPTR18M Mega-Truss Pick 18 inch for Threaded Rod Installations, Silver
MTPTR11.4375 Mega-Truss Pick 11.4375 inch for Threaded Rod Installations, Silver
MTPTR20.5M Mega-Truss Pick 20.5 inch for Threaded Rod Installations, Silver
MTPTR12M Mega-Truss Pick 12 inch for Threaded Rod Installations, Silver
MTPTR11.4375B Mega-Truss Pick 11.4375 for Threaded Rod Installations, Black Anodized
MTPTR20.5B Mega-Truss Pick, Install 20.5", Black, Black
MTPTR12W Mega-Truss Pick 12 inch for Threaded Rod Installations, White Powder Coat

The Light Source, Inc. 3935 Westinghouse Blvd. Charlotte, NC 28273 Phone: 704-504-8399 Fax: 704-588-4637
www.thelightsource.com