



### LIGHT SOURCE TYPE

- 19x Osram 40W RGBW LEDs.
- 1900 lumen each LED
- LED life expectancy: 50000Hrs ( 20000Hrs L70\* )  
\*It may vary depending on various factors, as type of use and environment

### PHOTOMETRIC DATA

- Zoom range: 4°- 50°
- 11401 Lumen Output (Integrating Sphere)
- High efficiency optical system

### NOISE LEVEL

- Theatre Fan mode: 34.5 dBA
- SLN Fan Mode: 35.2dBA
- Auto Fan Mode: 39.2 dBA
- Constant Fan mode: 41.2 dBA

### CONTROL and CONNECTIONS

- Personalities: 4 modes with 17/21/25/37 control channels
- Control Protocol: DMX, Art-Net, RDM, sACN
- DMX and RDM connectors: Locking 5 pin XLR IN/OUT
- Ethernet port: RJ45 IN
- Power connector: PowerCon True1 IN
- Built In Web Server

## **DYNAMIC EFFECTS**

- Colours:
  - Linear RGBW
  - Linear CTO (2500K to 8000K color temperature control)
  - Preset Macro colors
  - Three independently controlled LED rings
- Movement:
  - Tilt: 270° - 16bit
  - Pan: 540° - 16bit
  - Automatic repositioning
  - Fast/Standard speed selectable by Function channel
  - Mechanical Pan/Tilt lock for safe transportation and maintenance
- Beam:
  - Motorized Zoom
  - Automatic repositioning when DMX is disconnected
- Dimmer/Shutter :
  - High resolution electronic Dimmer - 24 bit (5 curves)
  - High speed electronic Strobe

## **HARDWARE and SOFTWARE**

- Long life self-charging battery
- Display Graphic LCD backlit b/w Display
- Firmware upload from another fixture
- Firmware Upgrade via Web Server
- Diagnostic
- DMX monitoring
- Remote access through RDM
- CloudIO compatibility

## **HOUSING**

- Aluminum and steel structure with plastic covers
- Two side handles for transportation
- IP20 protection rate

## **WORKING POSITION**

- Working in any position
- Hanging system: with fast-lock omega clamps (1/4 turn) on the base pn 183102/805
- Optional safety chain

## **ELECTRICAL**

Operating Voltage: 100-240V, 50/60 Hz

- Power Supply: Electronic auto range with active PFC
- Max Power consumption: 830VA

### **THERMAL SPECIFICATION**

- Max ambient temperature 45°C (113°F)
- Min ambient temperature -20°C (-4°F)
- Max temperature of the external surface 90°C (194°F)
- Total heat dissipation: 2596 BTU/hr ±10% / 2736 kJ/hr ±10%

### **SAFETY SPECS**

- Minimum distance of illuminated objects 0.2 meters (8")
- Minimum distance from flammable materials 0.2 meters (8")
- Fuse T10A – 250V
- Thermally protected power supply (overheating and cooling failure)
- Forced ventilation with axial fans

### **COMPLIANCE**

In conformity with the European Directives:

- 2014/35/EU - Safety of electrical equipment supplied at low voltage (LVD)
- 2014/30/EU - Electromagnetic Compatibility (EMC)
- 2011/65/EU - Restriction of the use of certain hazardous substances (RoHS)
- 2009/125/EC - EcoDesign requirements for Energy-related Products (ErP)
  
- cMETus Listed

### **PACKAGING**

- Carton box + Polystyrene
- Carton box + Foam shell
- Flight case + Foam shell (4 positions)

### **WEIGHT - SIZE**

- 17 Kg (37.5 lbs)
- 252x390mm (base dimension) – 471mm with vertical head (h)
- Distance between two fixtures 500mm

### **ACCESSORIES**

- Omega clamps: 2x183102/805 (included)
- Power cord: CAB03D/802 (included)
- Foam shell: F21321/001 (optional)
- Flight case: F21321 (optional)
- Safety Chain: 105041/003 (optional)