



The **PALADIN Brick™** is a compact and powerful outdoor flood light for a wide variety of applications. Using 24x15W RGBW cells it provides a total output of up to 8,200 lumens. Certified to IP65 it features a rugged design with a solid build quality, eliminating the need to worry about dust and water ingress. IP rated connections make it an ideal product to illuminate large areas of any outdoor event with vibrant and powerful colors. It can be operated standing on the floor or be hung in any orientation using the provided omega brackets. Cell control, strobe, Elation's E-FLY™ Internal Wireless DMX Transceiver, and removable frost filter features make the PALADIN Brick also a versatile effects fixture or audience blinder.

FEATURES

RGBW Flood Light

3x2 Cell Control

Removable Frost Filter

Rugged IP65 Design for Outdoor Events

Floor Standing or Mountable in any Orientation

Elation's E-FLY™ Internal Wireless DMX Transceiver



Removable Frost Filter

SPECIFICATIONS

SOURCE

(24) 15W RGBW LEDs

Up To 50,000 Hours Lamp Life*

*Test Labe Conditions. May vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, Dimming, and Lamp Mode.

PHOTOMETRIC DATA

6,000K Color Temperature

8,200 Total Lumen Output

14.1° Beam 25.4° Field Angle (without diffuser)

25.3° Beam 50° Field Angle (with diffuser)

COLOR

RGBW

CONTROL / CONNECTIONS

11 DMX Channel Modes (56 total channels)

3x2 Cell Control

Manual Tilt Adjustment

900 - 25,000 Hz DMX Adjustable Refresh Rate

4 Button Control Panel

180° Reversible OLD Menu Display

DMX and RDM Protocol Support

Elation's E-FLY™ Internal Wireless DMX Transceiver

IP65 5pin XLR DMX In/Out

IP65 Power In/Out

SIZE / WEIGHT

Length: 17.2 in (438mm)

Width: 5.8 in (147mm)

Height: 11.3 in (286mm)

Weight 21 lbs (9.5kg)

ELECTRICAL / THERMAL

AC 100-240V - 50/60Hz

390W Max Power Consumption

5°F to 113°F (-15°C to 45°C)

APPROVALS / RATINGS


CE | IP65



ORDERING INFORMATION

PAL264	Paladin Brick
PALADIN BRICK BARNDOOR	Barn Door
PALADIN BRICK SHADER	Shader
PALADIN BRICK FILTER 20°	20° Filter
PALADIN BRICK FILTER 60°	60° Filter
PALADIN BRICK FILTER 100°	100° Filter
PALADIN BRICK FILTER 40x1°	40x1° Filter
PALADIN BRICK FILTER 60x10°	60x10° Filter
PALADIN BRICK FILTER 1X40°	1X40° Filter
PALAXIN BRICK FILTER 10X60°	10x60° Filter

DIMENSIONS



PIXEL ZONE CONTROL

STANDARD

