

RDM10

TECHNICAL DATA REV A

OBSIDIAN™
CONTROL SYSTEMS



KEY FEATURES

- 10 assignable DMX outputs
- Integrated 2 Universe Artnet/sACN node
- Configurable DMX refresh rate
- Dual DMX Inputs for backup and signal loss options
- Remote configuration via internal webpage
- 1.8" OLED Display with rotary knob
- 99 Internal cues with fade and delay time
- Contact closures for cue or preset recall
- Powder-coated aluminum rackmount housing

SPECIFICATIONS

MOUNTING

Rackmount

CONNECTIONS

Front

- ((2) 5pin DMX Input
- (10) 5pin Opto-Isolated DMX Outputs
- Full color OLED display
- Encoder w. Push to Select / Exit Button

Back

- (2) 5pin DMX Input (parallel with front)
- (2) 5pin DMX Through
- (2) Locking RJ45 Ethernet Network In
- (10) Contact Closures (Terminal Block)
- Locking Power In/Thru

PHYSICAL

- Length: 482.5 mm (19 in.)
- Width: 146 mm (5.7 in.)
- Height: 44 mm (1.7 in.)
- Weight: 1.82 kg (4 lbs)

ELECTRICAL

- 100-240 V nominal, 50/60 Hz
- POE 802.3af

APPROVALS/RATINGS

cETLus / CE / IP20

RDM10

ORDERING

INCLUDED ITEMS

1.5m Locking power cable (EU or US version)

SKU

US #: NRD101

EU #: 1330000063

RD10

