

Eluxtra[™] 16 Bit XXL Pixel LED Strip Light, RGBW - Black Finish, 24V

RGBXX-PXXL-16B-72-24V-B-5m, RGBA-PXXL-16B-72-24V-B-5m



PRODUCT DESCRIPTION

Eluxtra™ 16-Bit XXL Pixel LED Strip Light is an advanced, high-performance lighting solution designed for exceptional color accuracy and seamless dimming. Featuring six LEDs per pixel, this strip delivers striking dynamic lighting effects and vibrant color gradients.

Its 16-bit control technology ensures highly precise brightness adjustment, enabling ultra-smooth dimming transitions. 72 LEDs per meter and cutting increments of 3.28 inches enable users to unlock the creative potential of linear lighting with high pixel resolution and reduced hotspots.

The black finish blends seamlessly into dark environments, making this an ideal product for theatrical and entertainment applications. Designed for professional installations, it operates at 24 VDC and is UL Listed for safety and reliability.

Ideal Application: Ideal choice for theatrical and entertainment installations that require exceptionally smooth dimming and color accuracy. This strip enables users to create custom lighting animations and color gradients, plus the black finish enables this strip to blend seamlessly into dark environments.



PRODUCT FEATURES

- 16-bit control for ultra-smooth dimming
- · 6 LEDs per pixel, 60 pixels per reel
- 480 channels per reel
- · IC chip UCS7604
- Sleek black finish blends seamlessly into dark environments
- Flexible and durable for versatile applications

REGULATORY

• UL Listed, RoHS Compliant

TECHNICAL SPECIFICA	TIONS		
Product Number	RGB65-PXXL-16B-72-24V-B-5m	RGB30-PXXL-16B-72-24V-B-5m	RGBA-PXXL-16B-72-24V-B-5m
Ambient Temperature	-20°C to 45°C	-20°C to 45°C	-20°C to 45°C
Average Lifetime	50,000 Hours	50,000 Hours	50,000 Hours
Beam Angle	120°	120°	120°
Brightness	1019 lm/m	934 lm/m	680 lm/m
Color Detail	Red, Green, Blue, 6500K	Red, Green, Blue, 3000K	Red, Green, Blue, Amber
Density	72 LEDs/m	72 LEDs/m	72 LEDs/m
Finish	Black	Black	Black
Height	0.08 in [2 mm]	0.08 in [2 mm]	0.08 in [2 mm]
Input Current	3750 mA	3750 mA	3750 mA
Input Voltage	24 DC	24 DC	24 DC
IP Rating	IP20	IP20	IP20
Lead Detail	Bare Wire / 200 mm (both)	Bare Wire / 200 mm (both)	Bare Wire / 200 mm (both)
Length	16.4 ft [5 m]	16.4 ft [5 m]	16.4 ft [5 m]
Min. Cutting Increment	3.28 in [83.3 mm]	3.28 in [83.3 mm]	3.28 in [83.3 mm]
Power (Watts/ft)	5.5 Watts/ft	5.5 Watts/ft	5.5 Watts/ft
Power (Watts/m)	18 Watts/m	18 Watts/m	18 Watts/m
Regulatory	UL, RoHS	UL, RoHS	UL, RoHS
Warranty	3 years limited	3 years limited	3 years limited
Width	0.47 in [12 mm]	0.47 in [12 mm]	0.47 in [12 mm]


Eluxtra™ products are exclusively available for purchase through Environmental Lights and City Theatrical.








MECHANICAL SPECIFICATIONS





Eluxtra™ products are exclusively available for purchase through Environmental Lights and City Theatrical.



