



SIDEWINDER

SPECIFICATIONS / TECHNICAL DATA REV A

KEY FEATURES

- 50,000 cu.ft/min
- (4) 8-Second 20' Bursts
- 180° Multi Position Fog Burst
- (22) 3w RGBA Leds
- Durable Tour-Ready Aluminum Housing

SPECIFICATIONS

PERFORMANCE

- Rated Power: 1450W
- Max Output: 50,000 CFM* (cu ft/min.)
- Max Continuous Output: 8 Seconds @ Full
- Max Throw Distance: 25 Feet
- Initial Ready Time: 9 Minutes
- Cycling Ready Time: 1 Minute
- Fluid Capacity: 2.5L
- Fluid Consumption: 180ml/min.

COMPATIBLE FLUID

- Atmosity Flash Fog Fluid (AFF-4L)
- Atmosity Extreme Filtered Fog Fluid (AEF-4L)

CONSTRUCTION

- Thermally Protected Heat Exchanger
- Advanced HPA (high pressure air) Pump Technology Energy Saving Mode with Auto-Clean Process Sealed Fluid Reservoir
- External Visual Fluid Level Detection
- Compact Light Weight Mobile Design

CONTROL

- 3 DMX Channel Modes (1 / 4 / 7)
- Onboard LCD Touch Control Panel
- DMX-512 and RDM Protocol Support
- Optional MagFLY Wireless DMX Transceiver
- Optional MagRF and Wired Remotes

CONNECTIONS

- 5-pin locking XLR, In/Out Data Connectors
- IP65 Locking Input Power Connector
- With Wired Digital Communication Network

SIZE / WEIGHT

- Length: 16.26 in. (413mm)
- Width: 7.60 in. (193mm)
- Height: 14.80 in. (376mm)
- Weight: 29.5 lbs. (13.4kg)



MAGMATIC



SIDEWINDER

SPECIFICATIONS / TECHNICAL DATA REV A

ELECTRICAL

Input Voltage: 120V, 230V, 240V 50/60Hz

9A (NFB) Resettable Breaker

Max Power Consumption: 1560W

THERMAL

Maximum Ambient Temperature (Ta max) 104°F (40°C)

Exterior Surface Temperature, Steady State: 140°F (60°C)

APPROVALS / RATINGS

CE | cETLus (pending) | IP20



MAGMATIC