

VDO ATOMIC BOLD

Acoustic Test Report



©2017-2021 HARMAN Professional Denmark ApS. Information subject to change without notice. HARMAN Professional and all affiliated companies disclaim liability for any injury, damage, direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document.

Martin®, HARMAN® and all other trademarks in this document pertaining to services or products by HARMAN Professional or its affiliates and subsidiaries are registered as the property of HARMAN Professional Denmark ApS.

HARMAN Professional Denmark ApS - Olof Palmes Allé 44 - 8200 Aarhus N - Denmark - www.martin.com

Martin[®]
by HARMAN

Title

VDO ATOMIC BOLD Acoustic Test Report

Test conditions

Test carried out according to ISO 3744:2010(E)

Device tested

Make: HARMAN Professional Denmark ApS

Model: VDO ATOMIC BOLD with Titan Fan

Serial no: 14620000013

Software version: V1.2.0

Results

An image of the test setup can be found on Page 3. Test results are listed in Table 1 on Page 5. Figures of measurement results are shown in Appendix A on Page 5.

HARMAN Professional Denmark ApS, R&D QA are responsible for the test results given in this report.

Environment

Temperature: 22.0°C Ta

Humidity: 64 %RH

AC mains power: 230 V, 50 Hz

Background noise level: 18 dBA

Warm-up time: 30 minutes at each test scenario

Fixture placement: Fixture was placed at least one meter from walls and ceiling, as described in the Standard ISO 3744:2010(E)

Remarks

Test results apply only to the tested specimen.

Rev: (last five)	Made by:	Description:	Approved by:	Date approved:
A	Justin XU	VDO Atomic Bold noise level measurement	Wouter Verlinden	2021/11/03

Setup

The product was placed indoors in a semi-anechoic room in the external Lab (See Figure 1). The ceiling and walls were all acoustically absorbent and the floor was reflective. The main dimensions of the room were 6.65m * 6.63m * 4.31m (length * width * height).




Figure 1: Test setup

The product was allowed a minimum 30 minutes of warm-up time before measurements were performed.

Measurement method

Measurements were carried out using a setup with 10 microphones.

Measurement setup at hemispherical measurement model, as figure 2



Key

- key microphone positions (1, 2, 3, 4, 5, 6, 7, 8, 9, 10)
- additional microphone positions (11, 12, 13, 14, 15, 16, 17, 18, 19, 20)
- A measurement surface
- B reference box

Figure 2: Microphone Positions

Note:

1. $R=2\text{m}$.
2. $S=2\pi R^2$, Measurement surface area: 25.12 m^2 .
3. 10 key microphones were taken measurement, as the range of A-weighted sound pressure levels measured at position 1 to 10 does not exceed 10 dB, additional 11 to 20 can be not considered.
4. The dimensions of the reference box: 38 cm x 36 cm x 32 cm.

Results

The VDO ATOMIC BOLD was measured in 3 different scenarios:

1. All effects static, Light source ON, 0% output white light – Constant Ultra-Low Fan Mode
2. All effects static, Light source ON, 100% output white light - Regulated Fan Mode
3. All effects static, Light source ON, 100% output white light - Constant Full Fan Mode

Test positions and sound pressure levels are shown in Table 1.

Distance from fixture	Constant Ultra-Low[dB(A)]	Regulated Fan [dB(A)]	Constant Full Fan [dB(A)]
LpA at 0m	27.2	33.9	51.7
LpA at 1m	19.2	25.9	43.7
LpA at 4m	7.1	13.9	31.7
LpA at 7m	2.3	9.0	26.8

The duration of the acoustical measurement for each position is 30s.

After calculated the time-averaged sound pressure levels of all positions and background noise, the difference between the two values is more than 15dB, therefore no correction for background noise shall be applied.

Table 1: Sound Pressure Levels

Sound Pressure Levels have been converted from Sound Power Levels using the formula: $LpA = (LWA - \text{reduction}_{\text{distance}})$

Reductions used: 8dB(A)@1m, 20dB(A)@4m, 24.9dB(A)@7m

Instrumentation

Equipment	Maker	Type
Semi-anechoic room	FAIST	
Microphone	Bruel &Kjaer	4165
Sound analyser	MNIPI	ASHV-004

Table 2: Instruments Used