

SPECIFICATION DATA

WAVECAST EIGHT



WaveCAST EIGHT is the new, multi-channel Wi-Fi assistive listening platform designed for larger assistive listening applications or for streaming audio in a bar, gym or other device where multiple sources of audio exist. The WaveCAST Eight is designed for pro-audio applications where high-quality sound is required for streaming multi-channel audio in real time to smartphones and/or tablets.

Up to 8 channels are available on a single WaveCAST EIGHT, and up to 4 WaveCAST EIGHTs can be used on one network.

Dimensions	17" W x 7.625" D x 1.72"H (43.18 cm x 19.37 cm x 4.4 cm)
Weight	5.0 lbs (2.27 kg)
Color	Black
Rack Mount	Standard 19" Rack, one EIA rack space high, one rack space wide
Power Supply	Desktop Style Transformer (TFP 062); Input: 100-240 VAC, 50/60 Hz. IEC Line Cord; Output: 24 VDC, 750 mA, 18W. 2.5mm ID center positive barrel connector
Power Switch	Rocker; backlit red indicates power on
Temperature Range	Operating: +32° F to +122° F (0° C to 50° C); Storage: -4° F to +158° F (-20° C to 70° C)
Audio Processor Functions	DSP based; Compression: 1:1, 1.5:1 or 2:1; High-pass and Low-pass Filter Frequency control
Frequency Response	31 – 16000 Hz, ±3 dB ("Music" Audio Preset)
Signal-to-Noise Ratio	Greater than or equal to 69 dB (streaming to Iphone)
Total Harmonic Distortion	Less than 0.25% @1 kHz
Common Mode Rejection	Greater than 52 dB @ 1 kHz
Audio Inputs	8 Phoenix-style Line Level Analog Audio, Balanced or Unbalanced Line Level
Audio Input Gain Adjust	In menu, adjustable to +6 to -60 dB, in 1dB steps
Ethernet	RJ-45 on back of unit supports CAT 5e cable lengths up to 328 feet (100 meters); 10/100 Base-T IEEE 802.3 compliant, unique MAC address
Approvals	FCC, RoHS3, WEEE, Industry Canada, CE, PSE, RCM, CB Scheme
Warranty	2-year parts and labor

WaveCAST EIGHT (WF T8)



Architectural Engineering Specs

WF T8

The WF T8 shall have a 3-pin Phoenix-style connector for audio inputs.

The WF T8 shall have a power source at 24VDC.

The WF T8 shall be housed in a 17" W x 7.625" D x 1.72"H (43.18 cm x 19.37 cm x 4.4 cm) device enclosure.

The WF T8 shall be covered by a two-year parts and labor warranty.

This product shall be the Williams AV model WF T8.

NOTE: SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

Domestic Sales

Williams AV 10300 Valley View Rd Eden Prairie, MN 55344 Ph: 800-328-6190 / 952-943-2252 FAX: 952-943-2174 Email: info@williamsav.com Web: www.williamsav.com

International Sales

International Sales Department Williams AV 10300 Valley View Rd Eden Prairie, MN 55344 USA Phone: +1 952 943 2252 Fax: +1 952 943 2174 Email: info@williamsav.com Web: www.williamsav.com

