

# Cloud 9X IP

## FEATURES

- Compact, professional fogger gives high-impact low-lying fog effect on stage or in ballrooms
- Suitable for temporary outdoor/wet use
- Continuous operation produces fog to cover 3,230 ft<sup>2</sup> (300 m<sup>2</sup>) area
- Ultrasonic agitators combine water with fog to produce low-lying fog effect
- Ships in integrated, rugged flight case with locking casters suitable for rental/touring applications with removable cover for rear panel
- Control via on board full color display, wireless (RF) handheld remote, or DMX
- Integrated water drainage system makes cleanup fast and easy
- Use the low-lying fog fluid (LLG) to produce the CO<sup>2</sup> effect, which lasts for several minutes before dissipating
- Use without dry ice or CO<sub>2</sub>, so no special licensing/training required
- USB-C slot for software uploads



## SPECIFICATIONS

### DYNAMIC EFFECTS

- Fan Performance: 81 cfm
- Low Fluid Shutdown: Yes

### CONSTRUCTION / PHYSICAL

- Dimensions (without back cover): 30 x 17.36 x 19.22 in (762 x 441 x 488.1 mm)
- Dimensions (with back cover): 37.72 x 17.36 x 19.22 in (958 x 441 x 488.1 mm)
- Output Nozzle (Outer Diameter): 4.76 in (121 mm)
- Hose Length (Fully extended): 11 ft (3.4 m)
- Weight: 76.6 lb (34.75 kg)
- Exterior Color: Black
- Housing Material: Aluminum alloy, High-impact flame-retardant polymer
- Water Tank Capacity (Primary Tank): 5.28 gal (20 l)
- Water Tank Capacity (Reserve Tank): 2.48 gal (9.4 l)
- Water Tank Capacity (Total): 7.77 gal (29.4 l)
- Tank Capacity (Low-lying Fog Fluid): 0.8 gal (3 l)
- Fluid Consumption: 27.8 ml/min
- Maximum Runtime: 2 hr

### CONNECTIONS

- Power Input: Seetronic Powerkon IP65
- Data Connectors: 3-pin/5-pin IP rated
- Cable Length (power): 5 ft (1.5 m)

- Firmware upgrades: USB type-C

## CONTROL

- Control Protocol: DMX, RDM, Wireless Remote
- DMX Channels: 3
- Modes/Personalities: 1 personality (3ch)
- On-Board Control: Yes
- Included Remote: Yes

## ELECTRICAL

- Input Voltage: 120 VAC, 60 Hz
- Input Voltage: 230 VAC, 50 Hz
- Power and Current: 1960 W, 17.5 A @ 120 V, 60 Hz
- Power and Current: 1281 W, 5.59 A @ 230 V, 50 Hz
- Heat-up Time: 5 min
- Breaker Size: 10 A, 250 V

## CERTIFICATIONS / QUALIFICATIONS

- CE, ROHS, UKCA
- IP Rating: IP54, temporary outdoor/wet use
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

## WHAT'S INCLUDED

- Cloud 9 X IP
- Seetronic Powerkon IP65 power cable
- RF remote (2-button)
- Hose clamps (x2)
- Barbed hose adapter (0.5 in)
- 6ft (2m) output hose, 5 in, (130 mm) diameter
- Removable rear cover
- Hose coupler, 5 in (130mm) diameter
- Floor nozzle, 5 in (130mm) diameter
- Overfill hose (polyurethane, 6mmOD, 4mm ID, 80 in / 204 cm)
- Quick Reference Guide

## OPTIONAL ACCESSORIES

- Neutrik powerKON cables
- DMX Cables