

COLORado Solo Edge 1

FEATURES

- Low-profile, 0.5mIP65 rated footlight with full-color and high-quality white light
- Single-source lens for smooth, even output with no distracting points of light and an additional "stealth" filter to help the fixture disappear when off
- Additional, fully controllable RGB marker lights can be used to cue talent or mark the edge of a stage
- Designed for end-to-end use with no gaps or distracting cable mess, and a covered display to keep everything elegant unseen.



SPECIFICATIONS

OPTICAL

- Light Source: 56 LEDs (Quintuple-color-RGBwWL), K 20,000 hours life expectancy
- Color Temperature (range): 2800 to 8000 K
- Color Temperature (at full): 6350K
- CRI (2800): 96.2
- Beam Angle: 111.1° (Horizontal)
- Beam Angle: 120.1° (Vertical)
- Field Angle: 134.1 ° (Horizontal)
- Field Angle: 161.4° (Vertical)
- Lumens: 7,144
- Illuminance (total): 104 lux @ 5 m
- PWM Frequency: 1000Hz, 2000Hz, 4000Hz, 6000Hz, 25KHz or 64KHz
- Selectable PWM: 1000Hz, 2000 Hz, 4000Hz, 6000Hz, 25KHz or 64KHz

DYNAMIC EFFECTS

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Framing Shutters: No
- Strobe Rate: 0 to 30Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Dim Modes: 4
- Dim Curves: 4
- Built-in Automated Programs: Yes
- Customizable Programs: Yes
- Recall Custom Programs: Yes/No

CONSTRUCTION / PHYSICAL

- Dimensions: 19.68 x 8.85 x 2.51 in (500 x 225 x 64 mm)
- Weight: 12.6 lb. (5.7kg)
- Exterior Color: Black

- Housing Material: Aluminum alloy and Aluminum diecast

CONNECTIONS

- Power Connection: Edison (Local) plug to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Power Output: Seetronic Powerkon IP65
- Data Connectors: 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)

CONTROL

- Control Protocol: Art-Net, DMX, sACN
- DMX Channels:
1 Cell: 5, 6, 6, 6, 6, 7, 11, 12, 12, 13, 14 or 21
2 Cell: 8, 9, 9, 10, 12, 19, 21, 22, 23 or 37
- Art-Net Channels:
1 Cell: 5, 6, 6, 6, 6, 7, 11, 12, 12, 13, 14 or 21
2 Cell: 8, 9, 9, 10, 12, 19, 21, 22, 23 or 37
- Modes/Personalities: Personalities (22)
- Frequency (operating): 1000Hz, 2000Hz, 4000Hz, 6000Hz, 25KHz or 64KHz

ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking:
- Power and Current: 126 W, 1.05 A @ 120 V, 60 Hz
- Power and Current: 125 W, .61 A @208 V, 60 Hz
- Power and Current: 125 W, .55 A @230 V, 50 Hz

CERTIFICATIONS / QUALIFICATIONS

- CE, MET, ROHS
- IP Rating: IP65, outdoor/wet, with pressure equalizing M6 GORE valve
- Temperature (Ambient): 5 °F to 113 °F (-15 °C to 45 °C)

WHAT'S INCLUDED

- COLORado Solo Edge 1
- Seetronic Powerkon IP65 power cord
- Power and Data linking cables
- Stealth Filter
- Omega bracket with mounting hardware

OPTIONAL ACCESSORIES

- Professional Clamps : CTC-50HC, CTC-50HCN
- Riglink TR1 Cables
- Riglink IP DMX cables
- Riglink IP Network cables