

COLORdash Accent 5X IP

FEATURES

- Hex-color (RGBWAUV) compact LED wash
- Extremely compact with excellent output and IP65-rated versatility
- Variable electronic dimmer (0-100%)
- Simple and complex DMX channel profiles with RDM for programming versatility
- Double-bracketed yoke doubles as floor stand
- Easy to use OLED digital display
- Replaceable filter for additional beam angles
- Built-in auto programs recalled via DMX or Master/Slave



SPECIFICATIONS

OPTICAL

- Light Source: 1 LED (Hex-color RGBWA+UV) 40 W, (950 mA), 50,000 hours life expectancy.
- Beam Angle w/ filter: 21.5°
- Field Angle w/ filter: 47.1°
- Beam Angle w/o filter: 11.4°
- Field Angle w/o filter: 20.4°
- Lumens: w/o filter: 890 lm
- Lumens: w/ filter: 733 lm
- Illuminance (total) w/ filter: 126 lux 5 m
- Illuminance (total) w/o filter: 618 lux @ 5 m
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

DYNAMIC EFFECTS

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 20 Hz
- Standalone Color Mixing: Yes
- Dim Modes: 5
- Built-in Automated Programs: Yes

CONSTRUCTION / PHYSICAL

- Dimensions: 7.24 x 5.70 x 3.46 in (184 x 145 x 88 mm)
- Weight: 2.8 lb. (1.3 kg)
- Exterior Color: Black

CONNECTIONS

- Power Connection: Edison plugs to hard-wired
- Power Input: Hard-wired
- Data Connectors: 5-pin XLR DMX input and output cable whips
- Cable Length (power): 5 ft (1.5 m)

CONTROL

- Control Protocol: DMX, RDM
- DMX Channels: 6, 8, 9, 13 or 14
- Modes/Personalities: 5 personalities (6, 8, 9, 13 or 14)

ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 44 W, 0.68 A @ 120 V, 60 Hz
- Power and Current: 44 W, 0.48 A @ 208 V, 60 Hz
- Power and Current: 43 W, 0.44 A @ 230 V, 50 Hz

CERTIFICATIONS / QUALIFICATIONS

- CE, MET, FCC, RoHS
- IP Rating: IP65, temporary outdoor/wet use with pressure equalizing M6 GORE valve
- Temperature (Ambient): 14 °F to 113 °F (-10 °C to 45 °C)

WHAT'S INCLUDED

- COLORdash™ Accent 5XIP
- Frosted filter

OPTIONAL ACCESSORIES

- Professional Clamps: CTC-50HC, CTC-50HCN
- 5-pin DMX Cables