

# Ocular

## Product Details

# elektraLite

## OVERVIEW

**Product Name**

elektraLite Ocular

**Model Numbers**

OCULAR RGBW  
OCULAR RGBWA  
OCULAR WW  
OCULAR CW

**Product Family**

eyeBall

**Product Type(s)**

LED, Wash

**Applications**

HOW, Live Events, Entertainment,  
Theater, Education

**Description**

A versatile powerhouse that can also function as a truss warmer, shin kicker, or house light, available in Cool White (CW), Warm White (WW), Quad (RGBW), and Five-in-One (RGBWA) options. Packed with a 100-watt COB LED light engine with a CRI of 95, it features a manual zoom with a range of 24.4 to 63.6 degrees for various optical effects. Store multiple shows effortlessly with adjustable speed and fade settings, and customize light dispersion with optional barn door accessory.

## SOURCE

**Light Source**

LED

**Number of Cells**

Quad (RGBW)  
5-in-1 (RGBWA)  
Single (Warm White)  
Single (Cool White)

**Light Engine**

100W COB LED

## COLOR

**Color Variations**

RGBW	RGBWA
WW	CW

**Color Mixing**

Available for all except WW & CW

**CRI or TM-30**

95 CRI

**Color Temperature**

W= 3200k for WW



elektraLite

70 Sea Lane, Farmingdale, NY 11735  
elektralitesupport@g1limited.com  
631-396-0184

myelektralite.com

# Ocular

## Product Details

elektraLite

### OPTICAL

**Zoom Range**

24.4 – 63.6

**Lens Options**

Manual Zoom

**Effects**

Strobe, Multiple Built-in Shows (w/ Speed and Fade Adjustments), 3 Dimming Curves and 4 inbuilt Dimming fade controls

### ELECTRICAL

**Total Power Consumption**

Max 275 watts

**Voltage Range**

100-240V 50-60 Hz

**Input Method**

PowerCon for both in and through

### CONTROL

**DMX Profile & Manual Control**

Please contact us at

[elektralitesupport@g1limited.com](mailto:elektralitesupport@g1limited.com)

for DMX Profiles and Photometrics

**Input Method**

DMX (5-pin) for both in and through

**RDM**

Yes

**Local Control**

Yes

**Display**

LCD with text display

**UI Type**

4-button navigation control

### SPECIFICATIONS

**Angles**

	<i>Minimum</i>	<i>Maximum</i>
<b>Beam angle</b>	24.4 degrees	51.0 degrees
<b>Field angle</b>	30.6 degrees	63.6 degrees



elektraLite

70 Sea Lane, Farmingdale, NY 11735

[elektralitesupport@g1limited.com](mailto:elektralitesupport@g1limited.com)

631-396-0184

[myelektralite.com](http://myelektralite.com)

# Ocular

## Product Details

elektraLite

### PHYSICAL

#### Dimensions

Front Lens Diameter 4 3/8"

	<b>Length</b>	<b>Width</b>	<b>Height</b>	<b>Weight</b>
<b>Body Only</b>	9 3/8"	10"	7 1/2"	7 LBS
<b>Body + Yoke</b>	13 1/2"	10"	12"	8 LBS

### OUTPUT

(Luminous Flux  $\pm$  10%)

#### RGBW

8,100

#### RGBWA

7,530

### OPTIONS

#### Accessories

Barn doors

#### Fixture Color

Black (Other colors available by request)

### REGULATORY

#### IP Rating

IP20 (Indoor)



elektraLite

70 Sea Lane, Farmingdale, NY 11735

elektralitesupport@g1limited.com

631-396-0184

myelektralite.com