

# Stingray Mini 20w

## Product Details

elektraLite

## OVERVIEW

### Product Name

Stingray Mini 20W

### Model Number(s)

SRAYM WW  
SRAYM CW  
SRAYM VW

### Product Family

Stingray Mini

### Product Type(s)

LED, Profile Spot

### Applications

Education, Entertainment, House of Worship,  
Live Events, Theater, Retail, Restaurants, &  
Commercial locations



### Description

A high performance and durable light fixture, the Stingray Mini is perfect for any environment requiring a reliable sophisticated lighting fixture at a competitive price point. From churches and schools to retail, commercial locations and more: it is a versatile light which is also aesthetically pleasing to the eyes.

## SOURCE

### Light Source

LED

### Number of Cells

Single source

### Light Engine

Single 20w COB LED module.  
Convection cooling through fin designed  
aluminum shell outer casing.  
Silent operation for quiet spaces.

## COLOR

### Color Variations

Warm White, Cool White & Variable White

### CRI or TM-30

≥95 CRI

### Color Temperature

Warm White 3000K  
Cool White 5000K  
Variable White 2800K to 6000K



elektraLite

70 Sea Lane, Farmingdale, NY 11735  
elektralitesupport@g1limited.com  
631-396-0184

myelektralite.com

# Stingray Mini 20w

## Product Details

elektraLite

### OPTICAL

#### Lens Options

19°, 26°, 36° & 50°

### ELECTRICAL

#### Total Power Consumption

25 watts (0.21A RMS @ 120v  
*(this is not inrush peak current)*)

#### Voltage Range

AC 100-240V – 50/60Hz

#### Input Method

Edison 120v plug for Standard & Canopy fixture.  
One Track 2 circuit track *(special order)*.

### CONTROL

#### DMX Profile & Manual Control

Please see the Product Data Page at  
<https://myelektralite.com/product-data-files>

#### Input Method

DMX-512 (in and thru) via 5 pin XLR

#### RDM

Remote Device Management (RDM)

#### Refresh Rate

Adjustable PWM in 0.1K increments  
From 0.55K to 25.0K

#### Local Control

Yes – Full control all functions without DMX.

#### Display

LCD with text display

#### UI Type

4-button navigation control

#### Dimming

0-100% for both DMX and local control.  
Dimming curve choices are provided within the power/dmx.



elektraLite

70 Sea Lane, Farmingdale, NY 11735  
elektralitesupport@g1limited.com  
631-396-0184

myelektralite.com

# Stingray Mini 20w

## Product Details

elektraLite

## PHYSICAL

### Housing

Aluminum monocoque design

### Materials

Aluminum

### Mounting Method

“C” clamp/threaded rod/pendant or canopy or track adapter.

### Dimensions

	<b>Length</b>	<b>Width</b>	<b>Height</b>	<b>Weight</b>
<b>Fixture Only</b>	13¼” (332.91mm)	5¾” (144.41mm)	4⅞” (102.47mm)	4.4lbs (2kgs)
<b>Fixture in Shipping Box</b>	16¼” (412.75mm)	7¾” (196.85mm)	6½” (165.1mm)	5½lbs (2.5kgs)

## REGULATORY

### IP Rating

IP20

## OPTIONS

### Accessories (*not included*)

Gobo holder, Color frame/Gel frame, DIN rail adapter.

A second 10ft extension cable (N.B. The maximum distance from the fixture to the standard power supply/dmx enclosure is 20 ft).

### Power Option

Both for the 30w & 80w, a power supply, with a 45 feet extension cable, maybe ordered either separately or instead of the standard power supply. The latter can only be done when ordering the fixture.

### Fixture Color

Black (*other colors available by request*)



elektraLite

70 Sea Lane, Farmingdale, NY 11735

elektralitesupport@g1limited.com

631-396-0184

myelektralite.com