

Stingray Mini IP65

Product Details (30W)

elektraLite

OVERVIEW

Product Name

Stingray Mini IP65 30W

Model Numbers

SRAYM WW 30W IP

SRAYM CW 30W IP

SRAYM VW 30W IP

SRAYM RGBW 30W IP

Product Family

Stingray Mini

Product Type(s)

LED, Profile Spot, IP-rated

Applications

Theme Parks, Outdoor Displays,
Retail, Advertising, Museums

**Description**

The Stingray Mini IP65 fixture range introduces a new era in the utilization of theatrical lighting fixtures, this time in the outdoor world. The fixtures are compact, yet sophisticated, with precision camera lensing. Ease of set up and control, either by DMX or on-board local management. Full IP65 rating makes it a success come rain or shine.

SOURCE

Light Source

LED

Number of Cells

Single Source

Light Engine

Single source 30w COB LED module

*Convection cooling through increased fin designed aluminum shell outer casing.
Silent operation for quiet spaces.*

COLOR

Color Variations

Warm White, Cool White, Variable White,
RGBW

CRI or TM-30

≥95 CRI

Color Temperature

WW (3000K)

CW (5000K)

VW (2800K-6000K)

(other CW/WW Kelvin choices are available)



elektraLite

70 Sea Lane, Farmingdale, NY 11735

elektralitesupport@g1limited.com

631-396-0184

myelektralite.com

Stingray Mini IP65

Product Details (30W)

elektraLite

ELECTRICAL

Operating Power Consumption

0.35A RMS @120v

(This is not inrush peak current)

Voltage Range

AC 100-250V – 50/60Hz

Input Method

Edison 120v plug standard. Other choices available (Special Order).

OPTICAL

Zoom Range

Choice of Zoom range 15°-30° or 25°-50° which are interchangeable.

REGULATORY

IP Rating: 65

ETL Certified

CONTROL

DMX Profile & Manual Control

Please visit:

<https://myelektralite.com/product-data-files>

Input Method

DMX-512 (in and thru) via 5pin XLR

RDM

Remote Device Management (RDM)

Refresh Rate

Adjustable PWM in 0.1K increments from 0.55K to 25.0K

Local Control

Yes – Full control all functions without DMX

Display

LCD with text display

UI Type

4-button navigation control

Dimming

0-100% for both DMX & Local control

Dimmer curve choices are provided within the power/DMX menu



elektraLite

70 Sea Lane, Farmingdale, NY 11735

elektralitesupport@g1limited.com

631-396-0184

myelektralite.com

Stingray Mini IP65

elektraLite

Product Details (30W)

PHYSICAL

Housing

- IP65 chassis design with power supply/DMX control enclosure separate
- Power supply/DMX control enclosure can be located away from the fixture
- Interchangeable lens carriage with rotating tube to adjust beam angles
- Housing also holds 4 shutter blades for perfect cuts, gobo slot, and a double slot for optional accessories

Materials

Marine grade aluminum

Mounting Method

Standard single "C" clamp

Din Rail Bracket for remote location of the power/DMX enclosure

Dimensions (Max Dimensions)

	<i>Length</i>	<i>Width</i>	<i>Height</i>	<i>Weight</i>
Fixture	15¾" (397.39mm)	7⅞" (172.55mm)	4¼" (102.47mm)	5lbs (2.18kgs)
Shipping Box	19" (480mm)	9" (230mm)	5¾" (145mm)	7¾lbs (3.5kgs)



elektraLite

70 Sea Lane, Farmingdale, NY 11735

elektralitesupport@g1limited.com

631-396-0184

myelektralite.com

Stingray Mini IP65

Product Details (30W)

elektraLite

OPTIONS

Accessories *(included)*

- Safety cable
- 10ft extension cable for remote locating the power supply

Accessories *(not included)*

- Gel/Color frame
- Gobo holder
- A second 10ft extension cable *(N.B. The maximum distance from the fixture to the standard power supply/DMX enclosure is 20 ft)*

Power Option

Power supply with a 45 feet extension cable may be purchased either separately or instead of the standard power supply. *Please specify when ordering the fixture.*

Fixture Color

Black

(Other colors available by special order)



elektraLite

70 Sea Lane, Farmingdale, NY 11735

elektralitesupport@g1limited.com

631-396-0184

myelektralite.com