Next-Generation 6-in-1 LED Par with Enhanced Optics and Features



Refined and Reliable

Building on the legacy of the HotBox™ EXA, the G2 delivers professional wash effects with 7x 15W 6-in-1 RGBAW+UV LEDs in a compact, durable housing. It introduces a host of new features, including upgraded 25° lenses that provide precise beam shaping and uniform color mixing, ensuring dependable performance for any stage, event, installation, or architectural application.

Advanced Control

With improved firmware and an easy-to-navigate OLED menu, this fixture offers 6/8/12-channel DMX profiles, built-in and customizable programs, a virtual color wheel, and 50 color presets including 32 Rosco® gel-matched selections. It also provides 5-pin DMX in/out, powerCON® TRUE1-compatible in/out, RDM support, plus 8 dimming curves and adjustable PWM refresh rates.

Luminous Intensity

Lux/M	2M	2.5M	3M	4M	5M
25°	3,499	2,230	1,523	893	537

Main Features

- RGBAW+UV color mixing via 7x 15W 6-in-1 LEDs
- Built-in auto programs + virtual color wheel
- 18 standard + 32 Rosco® matched color presets
- 6/8/12-channel DMX profiles
- 8 user-selectable dimming modes
- User-selectable PWM refresh rates
- Flicker-free constant-current LED driver
- RDM (Remote Device Management)
- 25 degree beam angle
- 4-button control menu with OLED display
- Dual brackets for mounting or stable freestanding
- 5-pin male/female XLR input/output connections
- PowerCON® TRUE1-compatible power input

Optical

7x 15W RGBAW+UV 6-in-1 LEDs, 100,000 hrs.

25° beam angle

Flicker-free LEDs

Weight & Dimensions

8” x 4.4” x 7.2” (203 x 110.8 x 183 mm)

4.25 lbs. (1.94 kg)

Control

USITT DMX-512, RDM

5-pin DMX in/out

6/8/12-channel DMX modes

4-button menu with OLED display

M/S, auto, sound active

Power + Current

90-240VAC, 50-60 Hz

Consumption: 78W, 1.1A, PF: .61

PowerCON® TRUE1-compatible in/out

Warranty + Certifications

2-year limited warranty