

# Maverick Force X Spot

## FEATURES

- Fully featured, compact and lightweight 520 W LED yoke spot fixture including CMY color mixing, a color wheel, zoom optics, and two gobo wheels: one rotating, and one static
- 16-bit dimming of master dimmer for smooth control of fades
- 65,000 PWM for use with the fastest frame cameras, but still maintains fantastic dimming
- Variable CMY color mixing system to create a wide pallet of colors
- DMX, CRMX, sACN, and Art-Net for full flexibility of control options
- RDM-enabled for remote addressing and trouble shooting
- 3.5° to 57.7° zoom range for variable beam sizes
- Iris, 5-facet prism, and frost for beam control
- True-1 compatible power input
- Three setup menu presets and preset sync for cross loading to multiple like fixtures for easy shop setup
- USB slot for software uploads
- Battery backup display with auto-rotate depending on fixture orientation
- Failsafe Ethernet connectivity allows data to pass even if fixture power is lost
- NFC for quick/easy fixture setup in the shop or in the field



## SPECIFICATIONS

### OPTICAL

- Light Source: 1 LED (CW) 520 W, (4.2 A), 6462 K, 50,000
- Color Temperature (at full): 6462 K
- Front lens diameters: 145 mm
- CRI: 72.2
- CRI with CRI filter: 90
- Beam Angle: 3.5° to 51.3°
- Field Angle: 3.7° to 56.3°
- Cutoff Angle: 3.9° to 57.7°
- Zoom Range: 3.5° to 57.7°
- Lumens - Output: 17,325
- Illuminance(3.5°) : 93,084 lux @ 5 m
- Illuminance (57.7°) : 1,135 lux @ 5 m
- Selectables PWM : 600Hz, 1500Hz, 2000Hz 65000Hz

### DYNAMIC EFFECTS

- Pan and Tilt: 540°/270°
- Pan and Tilt ranges: 540°, 360°, 180° pan/270°, 180°, 90° tilt
- Colors: 7 (including CRI and CTB filters) + white, split colors, continuous scroll at variable speeds

- Colors: CMY wheels
- Color Macros: # macros
- Gobos (1): 7 + open (1 metal + 6 glass), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds
- Gobos (2) 9+ open (9 metal) continuous scroll at variable speeds
- Gobo Size: Gobo Wheel 1 (rotating): 24 mm (outside), 14 mm (image), 1.1 mm (max. thickness)
- Dimmer: Electronic
- Shutter/Strobo: Electronic
- Zoom: Motorized
- Focus: Motorized
- Frost: Motorized
- Iris: Motorized
- Prism: 5-facet, motorized, rotating
- Strobe Rate: 0 to 25 Hz
- Move-in-Black: yes
- Dim Curves: 5

## CONSTRUCTION / PHYSICAL

- Dimensions: 14.21 x 9.40 x 25.43 in (361 x 239 x 646 mm)
- Weight: 44.2 lbs (20 kg)
- Exterior Color: Black
- Housing Material: Aluminum die-cast, High-impact flame-retardant polymer, Steel

## CONNECTIONS

- Power Connection: Edison plug to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Power Output: Seetronic Powerkon IP65
- Data Connectors: 3- and 5-pin IP65 XLR, Seetronic etherCON
- Cable Length (signal): 5 ft (1.5 m)

## CONTROL

- DMX Channels: 22 or 29
- Art-Net Channels : 22 or 29
- Modoos/Personalities: 2 personalities (22, 29)

## ELECTRICAL

- Input Voltage: 100 a 240 VAC, 50/60 Hz
- Power Linking: 2 units @ 120 V; 4 units @ 208 V; 5 units @ 230 V
- Power and Current: 554 W, 4.64 A @ 120 V, 60 Hz
- Power and Current: 541 W, 2.68 A @ 208 V, 60 Hz
- Power and Current: 542 W, 2.44 A @ 230 V, 50 Hz

## BATTERY

- Battery type: Lithium Ion (display screen backup)
- Rechargeable: Yes
- Battery Charge Time: 5 hours
- Battery Life: 1 hour
- Battery Power: 3.7 V, 500 mAh

## CERTIFICATIONS / QUALIFICATIONS

- CE, MET, FCC, UKCA
- IP Rating: IP20, dry location

- Temperature (Ambient):-4 °F to 113 °F ( -20 °C a 45 °C )

## WHAT'S INCLUDED

- Maverick Force X Spot
- Seetronic Powerkon power cable
- Omega brackets with mounting accessories

## OPTIONAL ACCESSORIES

- Clamps
- RigLink IP65 powerCON cables
- RigLink etherCON cables
- DMX cables
- Flight Cases
- CP Rack
- PowerStream 4 IP