

# IP65-Rated, RGBALC LED Par with **Battery and Wireless CRMX**

## **Built to Impress**

Like our Outpost™ RGBALC fixtures, the "Ranger" variation is powered by 3x 20W RGBALC 6-in-1 LEDs for bright, vibrant color mixing. Its fanless, convection-cooled design is slightly longer to accommodate a rechargeable lithium-ion battery and built-in CRMX wireless DMX receiver, offering greater flexibility for both indoor and outdoor applications.

## **Fully Equipped**

These fixtures offer 6/8/12-channel DMX modes + an intuitive 4-button OLED control menu with built-in programs, color presets, 32-bit dimming, and virtual color wheel. They come with 5-pin DMX input/output, a powerCON® TRUE1™ compatible input, and a single bracket for versatile rigging or freestanding use. For added convenience, an IR remote control is also included.

## **Luminous Intensity**

		· · · · · · · · · · · · · · · · · · ·				
	Beam	2M	2.5M	3M	4M	5M
	25° ,	3,927	2,495	1,716	950	592



### **Main Features**

- Light source: 3x 20W RGBALC 6-in-1 LEDs
- 25-degree beam angle
- Flicker-free constant-current LED driver
- Built-in 2.4Ghz CRMX wireless DMX receiver
- Intelion™ lithium-ion battery system
- Built-in auto programs + virtual color wheel
- 6/8/12-channel DMX profiles with 32-bit dimming
- IP65-rated outdoor LED fixture
- 4-button control menu with OLED display
- IR remote controllability (remote included)
- 5-pin DMX input & output connections
- PowerCON® TRUE1™ compatible power input
- Single bracket for rigging or freestanding
- Omega mounting points (bracket sold separately)



Optical

3x 20W RGBALC 6-in-1 LEDs, 100,000 hrs.

25° beam angle

Flicker-free LEDs



Weight & Dimensions

7.5" x 5.7" x 9.4" (190 x 143.8 x 239.4 mm)

7.5 lbs. (3.4 kg)



Control

USITT DMX-512, RDM

5-pin DMX in/out

6/8/12-channel DMX modes

4-button menu with OLED display

DMX512, M/S, auto mode



Power + Current

100-240VAC, 50-60 Hz

Consumption: 50W, .43A, PF: .99

Built-in 18650 capacity lithium-ion battery

PowerCON® TRUE1compatible input



Warranty + Certifications

2-year limited warranty













