







С	I-MM3-II PRODUCT SPECIFICATIONS
NOMINAL IMPEDANCE	8 Ω
SENSITIVITY dB @ 2.83V/1M	88 dB
FREQUENCY RESPONSE	82 Hz - 22 kHz
RECOMMENDED POWER	5 - 60 Watts
TWEETER	N/A
MIDRANGE	N/A
W00FER	3" (76.2 mm) Polypropylene w/ NBR Surround
ENCLOSURE MATERIAL	ABS Baffle
ENCLOSURE TYPE	Infinite Baffle
INPUTS	Screw Terminals
GRILLE	White & Almond Powder-Coated Aluminum (Fits Standard Dual Gang Box)
DIMENSIONS	4.125" (104.8 mm) H x 4.125" (104.8 mm) W x 1.9" (48.3 mm) D
CUTOUT DIMENSIONS	2.875" (73.1 mm) H x 3.5" (88.9 mm) W
MOUNTING DEPTH	1.875" (47.6 mm)
WEIGHT	1.5 lbs
SHIPPING WEIGHT	4 lbs
OPTIONAL ACCESSORIES	N/A
REGULATORY - CE	Approved
RoHS	Approved

Description:

The C-MM3-II is a raw frame 3-inch in-wall speaker that fits into a standard dual-gang box or mud ring.

Features:

- One 3 inch full-range polypropylene driver with butyl rubber surround
- Limited Lifetime Warranty
- Absolute Phase Crossover Network
- Auto-Reset Overload Protection
- Weatherized For Indoor/Outdoor Use
- Powder-Coated Aluminum Grilles in White and Almond

Applications:

Engineered for home theater or distributed audio applications where high-efficiency, added bass response and rapid installation are critical. The CI-MM3-II is ideal for any setting where full-range intelligilibity and installation ease is paramount, such as kitchens, foyers, bathrooms, hallways and patio/pool areas.

Warranty Information:

The CI-MM3-II comes with a limited lifetime warranty. Products not sold through an authorized dealer/distributor will not be supported by the factory warranty. Warranties are non-transferable.

Phase Technology:

8005 W 110th St Suite 208

Overland Park, KS 66102

Phone: 913.663.5600 Toll Free: 855.663.5600 Fax: 913.663.3200

www.phasetech.com