



	CS-8R PRODUCT SPECIFICATIONS
NOMINAL IMPEDANCE	8Ω
SENSITIVITY dB @ 2.83V/1M	87 dB
FREQUENCY RESPONSE	42 Hz - 20 kHz
RECOMMENDED POWER	5 - 120 Watts
TWEETER	.75" (19.05 mm) Variable Axis Soft Dome
MIDRANGE	N/A
WOOFER	8" (203.2 mm) Polypropylene w/ NBR Surround
ENCLOSURE TYPE	Infinite Baffle
INPUTS	Metal Push Terminals
GRILLE	White Powder-Coated Magnetic Micro-Flange (paintable)
DIMENSIONS	10.625" (269.9 mm) Diameter x 3.875" (73mm) Depth
CUTOUT DIMENSIONS	9.625" (244.5 mm) Diameter
MOUNTING DEPTH	3.375" (85.73 mm)
WEIGHT	4.75 lbs
SHIPPING WEIGHT	6 lbs
OPTIONAL ACCESSORIES	Pre-Construction Bracket (AC-CS-8R-PCB), Square Micro-Flange Grille (CI7X-SG)
REGULATORY - CE	Approved
RoHS	Approved

Description:

The CS-8R is an 8" coaxial in-ceiling speaker which delivers high-end performance for home theater or distributed audio applications.

The .75" variable axis tweeter allows high frequencies to be directed to the listener in situations where placement is less than optimal.

A round, magnetic micro-flange grille is included in the box, with a square grille (CI7X-SG) available as an optional accessory. All grilles are paintable and resistant to rust and corrosion.

Features:

- One 8.0 inch polypropylene woofer with butyl rubber surrounds and a .75" soft dome tweeter
- One .75" Variable Axis Soft Dome Tweeter in an Offset Design
- Limited Lifetime Warranty
- Auto-Reset Overload Protection
- Absolute Phase Crossover Network
- Ultra-Thin Magnetic Micro-Flange Grille
- Optional accessories: pre-construction bracket (AC-CS-8R-PCB), square microflange grille (CI7X-SG)

Applications:

Engineered for home theater or distributed audio applications indoors or out (as long as it is not exposed to direct heavy weather). The CS-8R pairs with Phase Velocity's V626.

Warranty Information:

The CS-8R comes with a limited ten (10) year warranty. Products not sold through an authorized dealer/distributor will not be supported by the factory warranty. Warranties are non-transferable.

Phase Technology:

8005 W 110th St Suite 208 Overland Park, KS 66102 Phone: 913.663.5600 Toll Free: 855.663.5600 Fax: 913.663.3200 www.phasetech.com