



Description:

The CI60 VIII is a 6.5" 2-way in-wall speaker which delivers true high-efficiency and performance across the operating bandwidth.

The 1" variable axis tweeter allows high frequencies to be directed to the listener in situations where placement is less than optimal.

Features:

- Limited Lifetime Warranty
- Auto-Reset Overload Protection
- Absolute Phase Crossover Network
- Magnetic Micro-Flange Grilles
- Left, Right, Center and Surround Applications

Applications:

Engineered for home theater or distributed audio applications where high-efficiency, added bass response and rapid installation are critical. The CI60 VIII pairs with the entire Premier Collection line.

Warranty Information:

The CI60 VIII comes with a limited lifetime warranty. Products not sold through an authorized dealer/distributor will not be supported by the factory warranty. Warranties are non-transferable.

CI60 VIII PRODUCT SPECIFICATIONS

NOMINAL IMPEDANCE	8Ω
SENSITIVITY dB @ 2.83V/1M	89 dB
FREQUENCY RESPONSE	38 Hz - 22 kHz
RECOMMENDED POWER	10 - 150 Watts
TWEETER	1" (25.4 mm) Variable Axis Soft Dome
MIDRANGE	N/A
WOOFER	6.5" (165.1 mm) RPF Flat-Piston Fiberglass & Kevlar Composite w/ NBR Surround
ENCLOSURE TYPE	Infinite Baffle
INPUTS	Gold-Plated Push Terminals
GRILLE	White Powder-Coated Galvanized Steel (paintable)
DIMENSIONS	11.81" (299.9 mm) H x 8.63" (219.2 mm) W x 3.9" (99.06 mm) D
CUTOUT DIMENSIONS	10.75" (273.1 mm) H x 7.5" (190.5 mm) W
MOUNTING DEPTH	3.5" (88.9 mm)
WEIGHT	4.75 lbs
SHIPPING WEIGHT	6 lbs
OPTIONAL ACCESSORIES	Back Box (BB-13-II), Rough-In Bracket (RB-18)
REGULATORY - CE	Approved
RoHS	Approved

Phase Technology:

8005 W 110th St
Suite 208
Overland Park, KS 66102
Phone: 913.663.5600
Toll Free: 855.663.5600
Fax: 913.663.3200
www.phasetech.com