

Lens	Angle	Distance									
		1m/3.3ft		3m/9.8ft		5m/16.4ft		7m/23ft		10m/32.8ft	
		Lux Center lx/fcd	Diameter m/feet	Lux Center lx/fcd	Diameter m/feet	Lux Center lx/fcd	Diameter m/feet	Lux Center lx/fcd	Diameter m/feet	Lux Center lx/fcd	Diameter m/feet
VN	Beam angle: 14,5°	213078/ 19796	0,3/0,8	23675/ 2200	0,8/2,5	8523/ 792	1,3/4,2	4349/ 404	1,8/5,9	2131/ 198	2,5/8,4
N	Beam angle: 23°	117411/ 10908	0,4/1,3	13046/ 1212	1,2/4	4696/ 436	2/6,7	2396/ 223	2,9/9,4	1174/ 109	4,1/13,4
M	Beam angle: 34,5°	55718/ 5176	0,6/2,1	6191/ 575	1,9/6,1	2229/ 207	3,1/10,2	1137/ 106	4,3/14,3	557/ 52	6,2/20,4
W	Beam angle: 48,9°	32794/ 3047	0,9/3	3644/ 339	2,7/8,9	1312/ 122	4,5/14,9	669/ 62	6,4/20,9	328/ 30	9,1/29,8
EN	Beam angle: 22,6°x16,3°	137792/ 12801	0,4x0,3/ 1,3x0,9	15310/ 1422	1,2x0,9/ 3,9x2,8	5512/ 512	2x1,4/ 6,5x4,7	2812/ 261	2,8x2/ 9,2x6,6	1378/ 128	4x2,9/ 13,1x9,4
EW	Beam angle: 54,5°x17,6°	56574/ 5256	1x0,3/ 3,4x1	6286/ 584	3,1x0,9/ 10,1x3	2263/ 210	5,1x1,5/ 16,9x5,1	1155/ 107	7,2x2,2/ 23,7x7,1	566/ 53	10,3x3,1/ 33,8x10,1