

Soundtube IPD-CM62-BGM-II-WH 6 inch IP-Addressable/Dante-Enabled In-Ceiling Speaker with Seamless Magnetic White Grille

Color	White
UPC	644216226603
Manufacturer	SoundTube
Manufacturer's Category	STNet IP-Addressable and Dante Series
Shipping Weight	9.5 lbs / 4.31 kg
Carton Height	8 in / 203.2 mm
Carton Length	13.25 in / 336.55 mm
Carton Width	13.25 in / 336.55 mm
Certifications	CE, RoHS, UL2043, UL60065, ETL-C/US
Enclosure Properties	ABS, Steel
Included Accessories	Conduit Clamp, Cover Plate, Grille, Paint Mask
Optional Accessories	Tile Bridge (AC-CMEZ6/8-TB) Pre-Construction Bracket (AC-CMEZ6/8-PCB) Junction Box (AC-CM-EZ-JBOX)
Source Inputs	RJ45 Ethernet Port
IP Rating	IPX3
Backcan Diameter	9.67 in / 245.6 mm
Backcan Height	5.75 in / 146.1 mm
Crossover Frequency	4.0 kHz
Directivity Factor (Q) (Averaged 100Hz - 10kHz, @ 2kHz)	5.1 and 5.0
Directivity Index (DI) dB (Averaged 100Hz - 10kHz, @ 2kHz)	6.2dB and 7.0dB
Frequency Response (± 10 dB)	60 Hz - 22 kHz
Frequency Response (± 3 dB)	55 Hz - 20 kHz
Grille Properties	Standard-Flange, Friction-Fit, White, Paintable, Painted, Steel
Low Frequency Voice Coil	1 in / 25.4 mm
Low Pass Crossover	12 dB per octave 2nd order
Max. Ceiling Thickness	1.6 in / 40.6 mm
Minimum Ceiling Thickness	0.04 in / 0.9 mm
Network Type: High Pass	12 dB per octave 2nd order
Tweeter Driver	1" Silk Dome w/ BroadBeam Ring®
Woofers Driver	6.5" Polypropylene Cone w/ Butyl Rubber Surround
Visible Diameter	298.5 mm
Visible Height	8.6 mm