

## Soundtube IPD-SM52-EZ-WX-BK 5.25 inch IP-Addressable/Weather-Resistant Dante-Enabled Speaker (Black)

<b>Color</b>	Black
<b>UPC</b>	752830435285
<b>Manufacturer</b>	SoundTube
<b>Manufacturer's Category</b>	STNet IP-Addressable and Dante Series
<b>Depth</b>	6.63 in / 168.4 mm
<b>Height</b>	11.88 in / 301.75 mm
<b>Width/Diameter</b>	7.5 in / 190.5 mm
<b>Shipping Weight</b>	7.8 lbs / 3.54 kg
<b>Carton Height</b>	12 in / 304.8 mm
<b>Carton Length</b>	15 in / 381 mm
<b>Carton Width</b>	10.5 in / 266.7 mm
<b>Certifications</b>	CE, IP65, RoHS, UL60065
<b>Included Accessories</b>	Mounting Hardware, Port Plug, Safety Cable
<b>Source Inputs</b>	RJ45 Ethernet Port
<b>IP Rating</b>	IP65
<b>Coverage Angle (<math>\pm 6\text{dB}</math> @ 2kHz)</b>	91° Horizontal / 120° Vertical
<b>Crossover Frequency</b>	3.5 kHz
<b>Directivity Factor (Q) (Averaged 100Hz - 10kHz, @ 2kHz)</b>	6.9 and 5.9
<b>Directivity Index (DI) dB (Averaged 100Hz - 10kHz, @ 2kHz)</b>	5.2 and 7.7
<b>Frequency Response (<math>\pm 10</math> dB)</b>	55 Hz - 20 kHz   Sealed: 62 Hz - 20 kHz
<b>Frequency Response (<math>\pm 3</math> dB)</b>	65 Hz - 20 kHz   Sealed: 80 Hz - 20 kHz
<b>Grille Properties</b>	Aluminum, Black, Powder-Coated
<b>Low Frequency Voice Coil</b>	25.4 mm (1") high temperature Kapton
<b>Max SPL @ 1M</b>	97 dB
<b>Tweeter Driver</b>	1" Soft Dome
<b>Woofers Driver</b>	5.25" Polypropylene Cone w/ Butyl Rubber Surround