

Soundtube IPD4-CM62-BGM-II-WH 6 inch IP-Addressable/4-Channel In-Ceiling Speaker with Seamless Magnetic Grille

Color	White
UPC	644216227006
Manufacturer	SoundTube
Manufacturer's Category	STNet IP-Addressable and Dante Series
Shipping Weight	9.6 lbs / 4.35 kg
Carton Height	8 in / 203.2 mm
Carton Length	13.25 in / 336.55 mm
Carton Width	13.25 in / 336.55 mm
Certifications	CE, UL2043, UL60065, ETL-C/US
Enclosure Properties	ABS, Steel
Included Accessories	Conduit Clamp, Grille, Tile Bridge
Optional Accessories	Tile Bridge (AC-CMEZ6/8-TB) Black Grille (GRL-CM-BGM-II-BK)
Source Inputs	6 Pin 5.08mm Euroblock, RJ45 Ethernet Port
IP Rating	IPX3
Backcan Diameter	9.67 in / 245.6 mm
Backcan Height	5.75 in / 146.1 mm
Crossover Frequency	4.0 kHz
Cutout Width/Diameter	11.75 in / 298.45 mm
Directivity Factor (Q) (Averaged 100Hz - 10kHz, @ 2kHz)	5.9 and 8.0
Directivity Index (DI) dB (Averaged 100Hz - 10kHz, @ 2kHz)	4.9 dB and 6.3 dB
Frequency Response (± 10 dB)	55 Hz - 20 kHz
Frequency Response (± 3 dB)	60 Hz - 20 kHz
Grille Properties	Standard-Flange, Friction-Fit, White, Paintable, Painted, Steel
Low Pass Crossover	12 dB per octave 2nd order
Max. Ceiling Thickness	2.5 in / 63.5 mm
Max SPL @ 1M	95 dB
Minimum Ceiling Thickness	0.035 in / 0.89 mm
Network Type: High Pass	12 dB per octave 2nd order
Tweeter Driver	1" Silk Dome w/ BroadBeam Ring®
Woofers Driver	6.5" Polypropylene Cone w/ Butyl Rubber Surround
Visible Diameter	11.75 in / 298.5 mm
Visible Height	0.34 in / 8.6 mm