



# IP65-Rated, RGB Pixel + White FX

### **Imminent Impact**

With a top and bottom row of 480x 0.5W RGB SMD 5050 LEDs and a center row of 240x 1W white SMD LEDs, the IP65-rated Sticknado™ Great White is designed to deliver an amazing display of colored pixels, strobe, and blinder effects. It also features DMX controllable electronic frost on the front lens. When applied, 0-100% diffusion of the RGB+W colors can be achieved.

### **Fully Loaded**

It offers a variety of channel modes, allowing full fixture wash effects or individual control of grouped LED pixels (up to 24 pixels per row). Multiple units can be aligned end-to-end with the included hardware, expanding design possibilities. With 33 built-in macros, 3 customizable programs, and smooth operation, this fixture excels in both stage and outdoor environments.

## **Luminous Intensity**

Beam	2.5M (clear)	2.5M (+frost)	5M (clear)	5M (+frost)
104°/110°	1,406	1,209	347	327

#### **Main Features**

- Color mixing via 480x 0.5W RGB SMD 5050 + 240x 1W white SMD LEDs
- Electronically controlled clear/frosted smart lens
- Viewing angle: 104° (110° with frost)
- Built-in color and pixel chase macros via DMX
- Virtual color wheel effects
- 33 built-in macros and 3 customizable programs
- IP65-rated outdoor LED fixture
- Efficient convection cooling
- Dual mounting brackets with locking knobs
- Interlocking housing design
- 5-pin DMX in/out + powerCON-compatible AC in/ out connections

Note: Sticknado™ Hammerhead and Sticknado™ Great White fixtures both share the exact same interlocking housing design, allowing them to be seamlessly connected together!



Optical

480x 0.5W RGB SMD 5050 LEDs

240x 1W white SMD LEDs

Electronic frost

Viewing angle: 104° (110° with frost)



Weight & Dimensions

39.4" x 5.9" x 6.6" (1000.3 x 149.4 mm x 167 mm)

19 lbs (8.6 kg)

 $[\dagger \downarrow \dagger]$ 

Control

USITT DMX-512, RDM

5-pin DMX in/out

Multiple DMX channel modes + pixel mapping

4-button menu with OLED display

DMX512, M/S, auto mode



Power + Current

100-240VAC, 50-60 Hz

Consumption: 358W, 3.15A, PF:.99

PowerCON® TRUE1compatible in/out



Warranty + Certifications

2-year limited warranty













