SWITCHBLADE FLIP

Dual-Faced RGBW Hybrid Moving Head with Infinite Pan & Tilt



Dynamic Beam, Wash, and Pixel Effects

The Switchblade™ Flip is a dual-faced moving head designed for powerful beam, wash, and pixel effects. One side features 4 x 60W RGBW 4-in-1 LEDs with a 2.5°–28° motorized zoom for tight or wide beams, while the reverse side combines 9 x 10W cool white LEDs with 108 x 0.5W RGB and 96 x 3W cool white SMD LEDs for striking strobe and pixel effects. The fixture also offers endless pan and tilt for unlimited motion and visual impact.

Endless Possibilities

It offers 20/34/93-channel DMX modes for precise control of 4 LED groups (A–D). Each group provides built-in programs with adjustable speed and strobe, all controllable via DMX or the LCD menu. Users also have access to 20 combined auto or sound-active programs for easy full-fixture effects. Additional features include RDM support, a rugged housing, 5-button LCD interface, 5-pin DMX, and PowerCON® TRUE1-compatible input.

Warranty

And of course, the Switchblade™ Flip is backed by Blizzard's 2-year limited warranty.

Main Features

- Dual-face hybrid beam/wash/pixel moving head
- 4 x 60W RGBW 4-in-1 LEDs with 2.5°–28° zoom
- 9 x 10W cool-white LEDs with 3.5° beams
- 108 x 0.5W RGB 5050 SMD LEDs
- 96 x 3W cool-white SMD LEDs
- Infinite pan and tilt movement
- Pan: 540°, Tilt: 270° (8/16-bit resolution)
- Pixel-mappable front and rear beams
- Eye-candy effects with speed and background control
- 0–30 Hz linear strobe effects
- DMX channels: 20/34/93-channel modes
- Operating modes: DMX512, M/S, auto, sound-active
- 5-button LCD control panel menu
- 5-pin DMX input/output
- PowerCON TRUE1-compatible power input

Optical

4x 60W RGBW LEDs (3.9° to 28° zoom)

9x 10W CW LEDs (3.5°), CCT = 10,000K

108x 0.5W RGB SMD LEDs

96x 3W CW SMD LEDs, CCT = 10,000K

Weight & Dimensions

11.4 x 7.8 x 19.4 in (289 x 198 x 493.7 mm)

22.8 lb. (10.4 kg)

Control

USITT DMX-512, RDM

5-pin DMX in/out

20/34/93-channel DMX modes

5-button LCD control panel menu

M/S, auto, sound active

Power + Current

100-240VAC, 50-60 Hz

Consumption: 370W, 3.26A, PF: .99

PowerCON® TRUE1-compatible in/out

Warranty + Certifications

2-year limited warranty